

Flat indicator lights

Rotation-proof

Option: waterproof IP64 / IP67 / IP68

Flach-Leuchten


Verdrehsicher

Option: wasserdicht IP64 / IP67 / IP68

Voyants lumineux plats

Anti-rotation

Option: étanche IP64 / IP67 / IP68



3D Step-file
available on request





343

344

348



Further specifications and options in section „E-G“ / Weitere Spezifikationen und Optionen in Kapitel „E-G“ / Autres spécifications et options au chapitre „E-G“

Type / Typ / Type		Body / Körper / Corps		Accessories Zubehör Accessoires	Lens / Linse / Lentille		Light source Lichtquelle Source lum.	Resistor Widerstand Résistance				
Terminals Anschlüsse Raccords		Protection Schutzart Protection	Surface Oberfläche Surface		with / mit avec Fresnel	Colour Farbe Couleurs	LED 5 mm	Code	V mA			
343		4	IP 64	B	Brass, blackened Messing, geschwärzt Laiton, noirce	A1	Amber Orange Orange	Y54U 7000 mcd	Yellow Gelb Jaune	0	without ohne sans	
		7	IP 67	S	Brass, nickel plated Messing, vernickelt Laiton, nickelée	B1	Blue Blau Bleue	Y50U 3000 mcd		A	5 20	
		8	IP 68	5	Stainless steel Edelstahl Acier inoxydable	C1	Clear Klar Claire	Y501 80 mcd		B	12 20	
				6	Stainless steel, blackened Edelstahl, geschwärzt Acier inoxydable, noirce	G1	Green Grün Verte	B91G 9000 mcd	Blue Blau Bleue	D	24 20	
344		8	IP 68	9	Brass, olive drab ** Messing, braunoliv ** Laiton, olivebrun **	R1	Red Rot Rouge	B21G 2120 mcd B61G 1160 mcd		E	28 20	
				5	Stainless steel 1.4305 Edelstahl 1.4305 Acier inoxydable 1.4305	 	W3	White Weiss Blanche	G81N 32500 mcd G71N 5620 mcd G501 80 mcd	Green Grün Verte	CL	9-48 20
							R54U 7000 mcd R50U 3000 mcd R521 80 mcd	Red Rot Rouge		CL1	5-28 20	
Type / Typ / Type		Body / Körper / Corps		Accessories Zubehör Accessoires	Lens / Linse / Lentille			Resistor Widerstand Résistance				
Terminals Anschlüsse Raccords		Protection Schutzart Protection	Surface Oberfläche Surface		with / mit avec Fresnel	Colour Farbe Couleurs		Resistor Widerstand Résistance				
348		4	IP 64	1	Brass, blackened Messing, geschwärzt Laiton, noirce	A1	Amber Orange Orange	W55N 22000 mcd W50N 2320 mcd	White Weiss Blanche	Z only Series 348*	230 5	
		7	IP 67	2	Brass, nickel plated Messing, vernickelt Laiton, nickelée	B1	Blue Blau Bleue	RGWW common cathode RGVW common anode only series 343, 348	Red- Green Rot-Grün Rouge- Verte			
		8	IP 68	5	Stainless steel Edelstahl Acier inoxydable	C1	Clear Klar Claire	P300 Phototransistor 420nm-1130nm				
				6	Stainless steel, blackened Edelstahl, geschwärzt Acier inoxydable, noirce	G1	Green Grün Verte	J484 IR-Diode 880nm, 50mW/sr				
				9	Brass, olive drab ** Messing, braunoliv ** Laiton, olivebrun **	R1	Red Rot Rouge					
Type / Typ / Type		Body / Körper / Corps		Accessories Zubehör Accessoires	Lens / Linse / Lentille			Resistor Widerstand Résistance				
Terminals Anschlüsse Raccords		Protection Schutzart Protection	Surface Oberfläche Surface		with / mit avec Fresnel	Colour Farbe Couleurs		Resistor Widerstand Résistance				
348		4	IP 64	1	Brass, blackened Messing, geschwärzt Laiton, noirce	A1	Amber Orange Orange	W55N 22000 mcd W50N 2320 mcd	White Weiss Blanche	Z only Series 348*	230 5	
		7	IP 67	2	Brass, nickel plated Messing, vernickelt Laiton, nickelée	B1	Blue Blau Bleue	RGWW common cathode RGVW common anode only series 343, 348	Red- Green Rot-Grün Rouge- Verte			
		8	IP 68	5	Stainless steel Edelstahl Acier inoxydable	C1	Clear Klar Claire	P300 Phototransistor 420nm-1130nm				
				6	Stainless steel, blackened Edelstahl, geschwärzt Acier inoxydable, noirce	G1	Green Grün Verte	J484 IR-Diode 880nm, 50mW/sr				
				9	Brass, olive drab ** Messing, braunoliv ** Laiton, olivebrun **	R1	Red Rot Rouge					

Operating Temperature -30° to +85°C (-40°C to +100°C on request) / Storage Temperature: -40° to +100°C

RoHS compliant / ** except surface option 9 (none RoHS)

Specifications are subject to change without notice – Änderungen die dem technischen Fortschritt dienen, sind vorbehalten – Réserve de modifications de toutes les données techniques

