

Indicator lights with reflector

Option: waterproof IP64 / IP67 / IP68

134

135


138

Signalleuchten mit Reflektor

Option: wasserdicht IP64 / IP67 / IP68

Voyants lumineux avec réflecteur

Option: étanche IP64 / IP67 / IP68



3D Step-file available on request

Further specifications and options in section „E-G“ / Weitere Spezifikationen und Optionen in Kapitel „E-G“ / Autres spécifications et options au chapitre „E-G“												
Type / Typ / Type	Body / Körper / Corps			Accessories / Zubehör / Accessoires		Light source Lichtquelle Source lum.	Resistor Widerstand Résistance					
Terminals Anschlüsse Raccords	Protection Schutzart Protection	Surface Oberfläche Surface	nut			LED 3 mm	Code	V	mA			
134 Solder lugs Lötösen Contact à souder	4	IP 64	B	Brass, blackened Messing, geschwärzt Laiton, noirecie	1 	0 front mounting	Y33U 4200 mcd Y30U 1200 mcd Y301 30 mcd	 Yellow Gelb Jaune	0	without ohne sans		
	7	IP 67	S	Brass, nickel plated Messing, vernickelt Laiton, nickelée					A	5	20	
	8	IP 68	9	Brass, olive drab * Messing, braunoliv * Laiton, olivebrun *					B	12	20	
135 LED terminals LED-Anschlüsse Fils des LED						B71G 6220 mcd B41G 1160 mcd	 Blue Blau Bleu	D	24	20		
								G41N 17600 mcd G51N 10320 mcd G301 40 mcd	 Green Grün Verte	DB	24	15
										E	28	20
138 Stranded wire Litze Fil multi-brins				1 	010 Standard (100 mm) Other lengths on request Andere Längen auf Anfrage Autres longueurs sur demande	R33U 4000 mcd R30U 1500 mcd R301 8 mcd	 Red Rot Rouge	EB	28	14		
								W37N 13350 mcd W36N 6900 mcd W32N 3745 mcd	 White Weiss Blanche	E	28	20
										RG36 common cathode only series 135 138 for 24V only 15mA for 28V only 14mA	 Red- Green Rot-Grün Rouge- Verte	EB
W32N	3745 mcd											

Operating Temperature -30° to +85°C (-40°C to +100°C on request) / Storage Temperature: -40° to +100°C

different LED's of the SLOAN range can be built in

RoHS compliant / * except surface option 9 (none RoHS)

Specifications are subject to change without notice - Änderungen die dem technischen Fortschritt dienen, sind vorbehalten - Réserve de modifications de toutes les données techniques

