



3D Step-file available on request

Indicator lights with reflector

Rotation-proof
Option: waterproof IP64 / IP67 / IP68

Signalleuchten mit Reflektor

Verdrehsicher
Option: wasserdicht IP64 / IP67 / IP68

Voyants lumineux avec réflecteur

Anti-rotation
Option: étanche IP64 / IP67 / IP68

353

354

358



Further specifications and options in section „E-G“ / Weitere Spezifikationen und Optionen in Kapitel „E-G“ / Autres spécifications et options au chapitre „E-G“

Type / Typ / Type	Body / Körper / Corps		Accessories Zubehör Accessoires	Light source Lichtquelle Source lum.	Resistor Widerstand Résistance
Terminals Anschlüsse Raccords	Protection Schutzart Protection	Surface Oberfläche Surface		LED 5 mm	Code V mA
353 LED terminals LED-Anschlüsse Fils des LED's	4 IP 64 7 IP 67 8 IP 68	B Brass, blackened Messing, geschwärzt Laiton, noircie	1	Y54U 7000 mcd Y50U 3000 mcd Y501 80 mcd Yellow Gelb Jaune	0 without ohne sans
		S Brass, nickel plated Messing, vernickelt Laiton, nickelée			
		5 Stainless steel Edelstahl Acier inoxydable	B 12 20		
		9 Brass, olive drab ** Messing, braunoliv ** Laiton, olivebrun **	6 Stainless steel, blackened Edelstahl, geschwärzt Acier inoxydable, noircie	D 24 20	
354 Faston 2.8 x 0.5	4 IP 64 7 IP 67 8 IP 68	5 Stainless steel, blackened Edelstahl, geschwärzt Acier inoxydable, noircie	5 Stainless steel 1.4305 Edelstahl 1.4305 Acier inoxydable 1.4305	B91G 9000 mcd B21G 2120 mcd B61G 1160 mcd Blue Blau Bleue	B 12 20 D 24 20
		9 Brass, olive drab ** Messing, braunoliv ** Laiton, olivebrun **			
		5 Stainless steel Edelstahl Acier inoxydable	9 Brass, olive drab ** Messing, braunoliv ** Laiton, olivebrun **	G81N 32500 mcd G71N 5620 mcd G501 80 mcd Green Grün Verte	CL 9-48 20 constant current only Series 354, 358
		6 Stainless steel, blackened Edelstahl, geschwärzt Acier inoxydable, noircie	5 Stainless steel Edelstahl Acier inoxydable	R54U 7000 mcd R50U 3000 mcd R521 80 mcd Red Rot Rouge	CL1 5-28 20 constant current only Series 354, 358
358 Stranded wire Litze Fil multi-brins	4 IP 64 7 IP 67 8 IP 68	1 Brass, blackened Messing, geschwärzt Laiton, noircie	1	W55N 22000 mcd W50N 2320 mcd White Weiss Blanche	Z 230 5 only Series 358*
		2 Brass, nickel plated Messing, vernickelt Laiton, nickelée			
		5 Stainless steel Edelstahl Acier inoxydable	9 Brass, olive drab ** Messing, braunoliv ** Laiton, olivebrun **	RGWW Red-Green Rot-Grün Rouge-Verte common cathode RGVW Red-Green Rot-Grün Rouge-Verte common anode only series 353, 358	
		6 Stainless steel, blackened Edelstahl, geschwärzt Acier inoxydable, noircie	5 Stainless steel Edelstahl Acier inoxydable	P300 Phototransistor 420nm-1130nm	
9 Brass, olive drab ** Messing, braunoliv ** Laiton, olivebrun **	5 Stainless steel Edelstahl Acier inoxydable	J484 IR-Diode 880nm, 50mW/sr			

Operating Temperature -30° to +85°C (-40°C to +100°C on request) / Storage Temperature: -40° to +100°C

different LED's of the SLOAN range can be built in

RoHS compliant / ** except surface option 9 (none RoHS)

*refer to installation instructions for 230V version in chapter „E“

Specifications are subject to change without notice - Änderungen die dem technischen Fortschritt dienen, sind vorbehalten - Réserve de modifications de toutes les données techniques

