



3D Step-file
available on request



Further specifications and options in section „E-G“ / Weitere Spezifikationen und Optionen in Kapitel „E-G“ / Autres spécifications et options au chapitre „E-G“

Type / Typ / Type		Body / Körper / Corps		Accessories Zubehör Accessoires		Cap / Farbkappe / Cabochon			Light source Lichtquelle Source lum.		Resistor Widerstand Résistance						
Terminals Anschlüsse Raccords		Protection Schutzart Protection		Terminals Anschlüsse Raccords		Style Form Forme		with/mit/ avec Fresnel Colour Farbe Couleurs		LED 5 mm		Code		V	mA		
175	<p>LED terminals LED-Anschlüsse Fils des LED's</p>	D	Body rotation-proof Körper mit Verdrehschutz Corps anti-rotation	3	LED terminals LED-Anschl. Fils des LED	1		1		A1	Amber Orange Orange		Y54U 7000 mcd	Yellow Gelb Jaune	0	without ohne sans	
										B1	Blue Blau Bleu		Y50U 3000 mcd				A
				6	Wire wrap posts Wire wrap Pfosten Poteaux Wire wrap	2		6		C1	Clear Klar Clair		Y501 80 mcd		B	12	20
										G1	Green Grün Vert		B91G 9000 mcd		D	24	20
										R1	Red Rot Rouge		B21G 2120 mcd				
				W3	White Weiss Blanc		B61G 1160 mcd	E	28	20							
				G81N 32500 mcd		D	24	20									
G71N 5620 mcd																	
G501 80 mcd																	
179	<p>Stranded wire Litze Fil multi-brins Standard 100 mm Other lengths on request Andere Längen auf Anfrage Autres longueurs sur demande</p>	D	Body rotation-proof Körper mit Verdrehschutz Corps anti-rotation	1	Stranded wire Litze Fil multi-brins	1		1		A1	Amber Orange Orange		R54U 7000 mcd	Red Rot Rouge	0	without ohne sans	
										B1	Blue Blau Bleu		R50U 3000 mcd				A
				6	Wire wrap posts Wire wrap Pfosten Poteaux Wire wrap	2		6		C1	Clear Klar Clair		R521 80 mcd		B	12	20
										G1	Green Grün Vert		W55N 22000 mcd		D	24	20
										R1	Red Rot Rouge		W50N 2320 mcd				
				W3	White Weiss Blanc		RG5F bipolar	E	28	20							
				G81N 32500 mcd		D	24	20									
G71N 5620 mcd																	
G501 80 mcd																	

Operating Temperature -30° to +85°C (-40°C to +100°C on request) / Storage Temperature: -40° to +100°C

different LED's of the SLOAN range can be built in

RoHS compliant

Specifications are subject to change without notice - Änderungen die dem technischen Fortschritt dienen, sind vorbehalten - Réserve de modifications de toutes les données techniques

