



Temperature/Process Controller Panel

CNI-CB120SB

1 YEAR
WARRANTY

- ✓ Easy-to-Use Digital Controller with On/Off, PID and Ramp/Soak
- ✓ Optional Ethernet Control with Built-In Web Server
- ✓ 120V Operation
- ✓ 12 A (1440 W) Nominal, 15 A Maximum Capacity
- ✓ Type K Input and M12 Female Connection Input for RTD or Process (0 to 1V, 0 to 10V, 4 to 20 mA)
- ✓ On/Off Switch
- ✓ Main Power Light
- ✓ Output 1 and Output 2 Indicator Lights
- ✓ Two 15 A Controlled Output Relays with Standard 120V Power Output Receptical
- ✓ Fuses for Controller, Output 1 and 2 Provided
- ✓ For Indoor Use

Hinged Metal Enclosure



CNI-CB120SB-K shown smaller than actual size, with CNI16D33 controller (included).



CNI-CB120SB-K-EI bottom with connections shown.

The CNI-CB120SB-K portable thermocouple temperature/process controllers are designed for indoor, general purpose use. Its design allows for a variety of temperature and process inputs.

Specifications

Weight: 4.53 kg (10 lb)

Dimensions: 203 H x 152 W x 152 mm D (8 x 6 x 6")

Operating Temperature: 0 to 55°C (32 to 151°F)

To Order Visit newportUS.com/cni-cb120sb for Pricing and Details

| Model No. | Description |
|------------------|---|
| CNI-CB120SB-K | Temperature/process single input controller with dual outputs |
| CNI-CB120SB-K-EI | Temperature/process single input controller with dual outputs and ethernet web server |
| Option | |
| M12-S-M-FM | M12 field mountable 4-pin with terminal lugs for wire connection |

Comes complete with CNI16D33 controller, one 1 A control fuse, one 15 A output fuse and two 5 A and 10 A fuses.

For different thermocouple input Type change "-K" in model number to "-J, -T, -E, -N, -R, or -S." Example: CNI-CB120SB-T, for Type T input.

Notes: If both outputs are used, the maximum output of both outputs combined is 15 A, since maximum input is 15 A.

Ordering Examples: CNI-CB120SB-K, temperature/process single input controller with dual outputs.

CNI-CB120SB-K-EI, temperature/process single input controller with dual outputs and ethernet web server.