
Metal Protection Tubes







ALL MODELS AVAILABLE FOR FAST DELIVERY!

To Order (Specify Model Number)							
Nominal ¾" Schedule 40 Black Steel Pipe (0.824" I.D. x 1.050" O.D.)				Nominal ½" Schedule 40 Black Steel Pipe (0.622" I.D. x 0.840" O.D.)			
Thread	Length mm (in.)	Model Number	Price	Thread	Length mm (in.)	Model Number	Price
34" NPT	300 (12)	3/4 - PTBS-12	\$57	½" NPT	300 (12)	1/2- PTBS-12	\$49
34" NPT	450 (18)	3/4 - PTBS-18	84	½" NPT	450 (18)	1/2- PTBS-18	72
34" NPT	600 (24)	3/4 - PTBS-24	112	½" NPT	600 (24)	1/2-PTBS-24	95
Nominal ¾" Schedule 40-304 SS Pipe (0.824" I.D. x 1.050" O.D.)				Nominal ½" Schedule 40-304 SS Pipe (0.622" I.D. x 0.840" O.D.)			
Thread	Length mm (in.)	Model Number	Price	Thread	Length mm (in.)	Model Number	Price
3/4" NPT	300 (12)	3/4-PTSS-12	\$67	½" NPT	300 (12)	1/2-PTSS-12	\$58
3/4" NPT	450 (18)	3/4-PTSS-18	1021	½" NPT	450 (18)	1/2-PTSS-18	86
¾" NPT	600 (24)	3/4-PTSS-24	135	½" NPT	600 (24)	1/2-PTSS-24	114

Technical Data

Male NPT thread on one end, spun closed on the other end

	Max. Continuous Mech. Strength						
	Material	Operating Temp.	Cold	Hot	Applications	Remarks	
	304SS	900°C (1650°F)	Excellent	Fair	Food processing, dairy products, petroleum products, mild acids, alkalies	Embrittles in 425°C (800°F) to 760°C (400°F) range.	
	Black Steel	650°C (1200°F)	Excellent	Good	Molten babbit, tin, lead and magnesium	Low cost	

[†]Other lengths and materials available, consult Sales Department.

Ordering Example: 3/4-PTSS-12, is a 300 mm (12") long metal protection tube of 304 stainless steel with a %" thread, **\$67**.

Mounting Flanges and Bushings with standard NPT thread available upon request. Consult Sales for pricing.

Discount Schedule				
1–10 Units Net	Quantity discount applies			
11–24 Units	to like tubes. Other sizes,			
25–100 Units	materials and configurations			
101 and upConsult Sales	by quotation.			