Multiprobe Switchbox For Handheld Thermocouple Thermometers

6 Inputs with Rotary Selector

Works with a Wide Variety of Handheld Meters

Two-Position Output Connector for Single and Dual Input **Thermometers**

Available for J, K and T Calibrations

The HH20SW is a compact. economical switchbox that lets you use your handheld meter with up to 6 próbes. A subminiature connector mates quickly and easily to most handheld thermometers, and can slide from side-to-side for use with single and dual input thermometers.

The HH20SW accepts 6-subminiature (SMP) male thermocouple connectors; a rotary switch let's you select the input channel quickly and easily. The HH20SW will operate with many thermocouple handhelds.

Specifications

Operating Ambient: 0 to 50°C; less than 90% RH to 35°C; reduce RH limit by 3%/°C from 35 to 50°C

Connectors: 1 male, 6 female subminiature

thermocouple connectors, type SMP

Dimensions: 127 H x 71 W x 38 D mm (5 x 2.8 x 1.5")

Weight: 341 g (12 oz)



and probe itely see and L-34

| | tano mododiomento ana cambrato pario motoro, |
|---|---|
| HH21 Meter sold separa pages L-33 | controllers and transmitters quickly and easily. You can store up to 10 temperatures in memory for fast recall. The CL25 features an easy-to-read 5-digit |
| To Order (S) | LCD with custom readouts for the operating mode. Other features include °C/°F switching, |
| Model Number | 0.1° resolution, 0.1% of reading accuracy, and power-off configuration retention, |
| HH20SW-(*) | where the instrument remembers the last selected thermocouple type, |
| SMP-(*)-M | units, resolution, operating mode |

and memory contents.

USA

The CL25 calibrator lets you both measure and simulate thermocouples in the lab or field. Use it to take measurements and calibrate panel meters.

> For complete specifications and features, see NEWPORT's complete line of CL20 Series calibrators.

| To Order (Specify Model No.) | | | |
|------------------------------|-------|-----------------------|--|
| Model Number | Price | Description | |
| HH20SW-(*) | \$149 | Multiprobe switchbox | |
| SMP-(*)-M | 1.75 | Mating male connector | |

*Specify calibration: J, K, or T

Ordering Example: HH20SW-J, multiprobe switchbox, SMP-J-M, mating male connector, \$149 + 1.75 = \$150.75