



USB OUTPUT PRESSURE TRANSDUCER CONNECT DIRECTLY TO YOUR COMPUTER

High Speed
1000 Updates/second

Gage and Absolute Pressures

10 inH₂O to 5000 psi

(25 mb to 345 bar)

Vacuum and Compound Ranges

10 inH₂O to 15 psi

Barometric Ranges



PX409 USB Series



Standard

- ✓ 1000 Updates per second
- ✓ Micro-Machined Silicon Sensor
- ✓ 316L SS Wetted Parts
- ✓ High $\pm 0.08\%$ Accuracy FS
- ✓ Fast Delivery! Stock to 1-Week on Most Models
- ✓ Excellent Long Term Stability
- ✓ USB 2.0 and Below Compatible
- ✓ Standard USB Connector Termination
- ✓ Shock and Vibration Rated
- ✓ Ruggedized with Secondary Containment

The PX409 USB Series connects directly to your computer. Free software makes data logging and charting your readings a simple task. Also included are drivers for popular laboratory programs plus some web applications. The micro-machined silicon design are ideal for pressure or level applications in laboratory, test platforms, or bio/pharmaceutical applications as well as industrial applications that require a rugged, high accuracy transducer. The micro-machined silicon sensor provides a very stable transducer with exceptional high accuracy of $\pm 0.08\%$ typical and a broad compensated range of -29 to 85°C (-20 to 185°F). The modular construction allows for fast delivery of most configurations and fittings. Delivery is typically stock to 1 week!

SPECIFICATIONS

Accuracy: 0.08% BSL typical (linearity, hysteresis and repeatability combined)

Temperature Compensation (Over Compensated Range):

Span: Range > 5 psi: $\pm 0.5\%$
Range ≤ 5 psi: $\pm 1.0\%$

Zero: Range > 5 psi: $\pm 0.5\%$
Range ≤ 5 psi: $\pm 1.0\%$

Minimum Isolation Between Case and, Output Terminations:
100 M Ω @ 50 Vdc (2 M Ω after EMI filter)

Pressure Cycles: 1 million, minimum

Long Term Stability (1-Year): $\pm 0.1\%$ FS typical

A to D Conversion: 24-bit

Shock: 50 g, 11 mS half sine, vertical and horizontal axis

FREE SOFTWARE INCLUDED!

Each unit includes free software that converts your PC into a strip chart recorder or data logger so readings can be saved and later printed or exported to a spread sheet file. Also included are software drivers for some of the most popular Laboratory programs.

Vibration: 5-2000-5 Hz, 30 minute cycle, Curve L, Mil-Spec 810 figure 514-2-2, vertical and horizontal axis

Bandwidth: DC to 1000 updates per second typical

CE Compliant: Meets industrial emissions and immunity EN61326

Environmental Protection: IP65

Secondary Containment Vacuum and Pressure:

10 inH₂O to 5 psi: to 1000 psi

15 to 1000 psi: to 3000 psi

1500 to 5000 psi: to 15,000 psi

Secondary Containment Absolute Pressure:

5 to 1000 psi: to 6000 psi

1500 to 5000 psi: to 15,000 psi

Wetted Parts: 316L SS

Weight: 200 g (7 oz)

Overpressure Gage Pressure:

10 inH₂O: 10 times span

1 psi: 6 times span

2.5 psi to 3500 psi: 4 times span

5000 psi: 15,000 psi max

Overpressure Absolute Pressure:

5 psia: 6 times span

15 psia to 3500 psia: 4 times span

5000 psia: 15000 psi max


Operating Temperature Range: -40 to 85°C (-40 to 185°F)

Compensated Temperature:

Ranges > 5 psi: -29 to 85°C (-20 to 185°F)

Ranges ≤ 5 psi: -17 to 85°C (0 to 185°F)

USB OUTPUT PRESSURE TRANSDUCER



To Order Visit newportUS.com/px409-usb for Pricing and Details

RANGE/RESOLUTION		GAGE PRESSURE MODEL NO.	ABSOLUTE PRESSURE MODEL NO.
psi	bar		
GAGE PRESSURE			
0 to 10.00 inH ₂ O	0 to 25.00 mb	PX409-10WGUSB	—
0 to 1.000	0 to 69.00 mb	PX409-001GUSB	—
0 to 2.500	0 to 172.0 mb	PX409-2.5GUSB	—
0 to 5.000	0 to 345.0 mb	PX409-005GUSB	—
0 to 15.00	0 to 1.000	PX409-015GUSB	PX409-015AUSB
0 to 30.00	0 to 2.100	PX409-030GUSB	PX409-030AUSB
0 to 50.00	0 to 3.400	PX409-050GUSB	PX409-050AUSB
0 to 100.0	0 to 6.900	PX409-100GUSB	PX409-100AUSB
0 to 150.0	0 to 10.30	PX409-150GUSB	PX409-150AUSB
0 to 250.0	0 to 17.20	PX409-250GUSB	PX409-250AUSB
0 to 500.0	0 to 34.50	PX409-500GUSB	PX409-500AUSB
0 to 750.0	0 to 51.70	PX409-600GUSB	PX409-600AUSB
0 to 1000	0 to 69.00	PX409-1.0KGUSB	PX409-1.0KAUSB
0 to 1500	0 to 103.0	PX409-1.5KGUSB	PX409-1.5KAUSB
0 to 2500	0 to 172.0	PX409-2.5KGUSB	PX409-2.5KAUSB
0 to 3500	0 to 241.0	PX409-3.5KGUSB	PX409-3.5KAUSB
0 to 5000	0 to 345.0	PX409-5.0KGUSB	PX409-5.0KAUSB
VACUUM RANGES (NEGATIVE GAGE PRESSURE)			
0 to -10.00 inH ₂ O	0 to -25.00 mb	PX409-10WVUSB	—
0 to -1.00 psi	0 to -69.00 mb	PX409-001VUSB	—
0 to -2.500 psi	0 to -172.0 mb	PX409-2.5VUSB	—
0 to -5.00 psi	0 to -345.0 mb	PX409-005VUSB	—
0 to -15.00 psi	0 to -1.000	PX409-015VUSB	—
COMPOUND GAGE RANGES			
± 10.00 inH ₂ O	± 25.00 mb	PX409-10WCGUSB	—
± 1.000 psi	± 69.00 mb	PX409-001CGUSB	—
± 2.500 psi	± 172.0 mb	PX409-2.5CGUSB	—
± 5.000 psi	± 345.0 mb	PX409-005CGUSB	—
± 15.00 psi	± 1.000	PX409-015CGUSB	—
BAROMETRIC RANGES (ABSOLUTE PRESSURE)			
0 to 32.00 inHg	0 to 1100 mb	—	PX409-32BUSB
16.00 to 32.00 inHg	550.0 to 1100 mb	—	PX409-16BUSB
26.00 to 32.00 inHg	880.0 to 1100 mb	—	PX409-26BUSB

Comes complete with 5-point NIST traceable calibration certificate, CD with charting and graphic software plus drivers.

Ordering Examples: PX409-100GUSB, 2 m (6') cable with USB termination, 100 psig range, USB output.

PX409-16BUSB, 2 m (6') cable with USB termination, 16 to 32 inHg absolute barometric range, USB output.