


SX-570/SX-580

Enterprise 802.11n Connectivity for Battery Operated Devices



Serial to Wi-Fi/Ethernet to Wi-Fi Modules

The SX-570/SX-580 high-performance Serial to Wi-Fi/Ethernet to Wi-Fi modules provide connectivity for low-power portable devices to 802.11 wireless local area networks (WLANS). Eliminating the need for the development of a wireless LAN driver and security supplicant, it is ideal for minimizing engineering investment and reducing time to market.

Measuring 1.18 x 2.16 inches (30 x 55 mm), the SX-570/SX-580 features a powerful 32-bit 454 MHz Freescale i.MX28 processor with an 802.11a/b/g/n radio, a complete TCP/IP network protocol stack, and an optimized AR6003 wireless radio driver and security supplicant in a self-contained hardware package. One major advantage of the SX-570/SX-580 is enterprise security, including WPA2 with 802.1x authentication, which enables it to be used on almost any customer's network without security compromises. Another key SX-570/SX-580 advantage is a full-featured Linux operating system that allows OEMs to easily offload requirements such as protocol conversion or data filtering using standard C programming.

The SX-570/SX-580 is designed to connect to a wide range of OEM devices without the need for special software drivers or interface hardware. It includes a serial port that can run at speeds up to 3 Mbps and supports Ethernet bridging and AP mode.

Key Features:

- Based on Qualcomm Atheros AR6003**
 This advanced chip technology enables the SX-570/SX-580 to provide breakthrough performance at the lowest cost.
- Reduced Power Consumption**
 The SX-570/SX-580 minimizes power while transmitting and receiving data (approximately 300mA) while its power management features reduce power usage during periods of inactivity.

- Industry-Leading Enterprise Security**

The SX-570/SX-580 supports WEP, WPA and WPA2 including 802.1x Extensible Authentication Protocol (EAP) types.

- Linux Operating System with User Programmability**

The SX-570/SX-580 uses the Linux operating system and is designed to allow users to easily add new features. With a 454 MHz processor and 64MB of RAM and 8MB of flash memory, the SX-570/SX-580 has plenty of capacity to handle complex user applications.

Specifications:

Product Name	SX-570-2700	SX-580-2700
CPU	Freescale i.MX280 ARM9/454 MHz	
Memory	8MB ROM/64MB RAM	
Radio Module	SX-SDMGN	SX-SDMAN
Radio Specifications	802.11b/g/n	802.11a/b/g/n
Operating System	Linux	
Security	WEP/WPA/WPA2 802.1x (LEAP, PEAP, TLS, TTLS, FAST)	
Interfaces	UART/Ethernet (USB/I2C/GPIO/SPI)	
Operating Voltage	5V +/-5%	
Operating Temperature	-20 to +85 degrees C	-10 to +70 degrees C
Dimensions	55.0 x 30.0 x 9.25 mm* (W x H x D)	

* Minimum height using lowest profile mating connector.

silex technology is a registered trademark of silex technology, Inc. Other product or brand names may be registered trademarks or trademarks of their respective owners. Technical information and specifications are subject to change without notice. © 2012 silex technology, Inc. All rights reserved.

silex global sales & support locations