

SX-10WG 802.11g/b Wireless mini-PCI-Module

For Reliable Embedded Wi-Fi Connectivity




Experience the Quality Global OEMs Trust

Key Features

- Maximum data transfer rate 54Mbps
- Powered by the Atheros AR5005G chipset
 - Highly Integrated all CMOS, single-chip IEEE 802.11g/b compliant
 - Includes a 2.4 GHz radio, analog-to-digital and digital-to-analog (ADC/DAC) converters, baseband processors, multi-protocol media access control (MAC), high speed UART and a PCI/CardBus host interface
- Includes 2dBi antenna and supports diversity antenna configurations
- Meets a wide range of global regulatory certifications / standards
 - ARIB STD-T66 FC - FCC Part 15 Subpart C
 - RCR STD-33 - IC RSS210
 - EU Directive R&TTE (EN300 328, EN60950)
 - RoHS (Restriction on Hazardous Substances) compliant
- Limited modular certification in U.S. and Canada
- Compliant to Mini PCI-Type III/F
- Superior quality from the Silex ISO 9001/2000 certified facility

Dimensions



SILEX facts

SILEX TECHNOLOGY is a 30-year developer of external and embedded device-device connectivity products. SILEX has become the world's #1 supplier of embedded wired and wireless connectivity products over the past 10 years, helping global OEMs improve the way they move information. SILEX advantages for OEMs include a support team, industry-leading software solutions like our NSS security suite, and exceptional Japanese quality manufacturing.

Specifications

Product Name	SX-10WG 802.11b/g miniPC Wireless LAN module
Chipset	Atheros AR5005G
Antenna connector	2 x U-FL connector + Diversity antenna
Operating Voltage	3.3V+/-0.3V
Radio Output	11g Modus: ch 1: 12dBm; ch 2: 16dBm; ch 3-4: 15,5dBm; ch 5-7: 15dBm; ch 8-10: 14,5dBm; ch 11-13: 14dBm 11b Modus: ch 1-14: 16dBm
Power Consumption	500mA 11g transmit: 3.3V 360mA 11g receive: 3.3V 290mA 11b transmit: 3.3V 350mA 11b receive: 3.3V 215mA Sleep mode: 20mA
Weight	12 g
Dimensions	44,6 x 59,6 x 4 mm Thickness of PCB: 1,0 mm
Temperature	Storage: -10 to + 70 °C Operating: 0 to + 60 °C
Relative Humidity	Storage: 5 to 90 % RH Operating: 20 to 90 % RH
Package contents	PCBA, Certification label, E/A label

SILEX TECHNOLOGY is a registered trademark of SILEX TECHNOLOGY, Inc. Other company or product names may be trademarks or registered trademarks of their respective owners. Technical information and specifications are subject to change without notice. © 2008 SILEX TECHNOLOGY EUROPE GmbH. All rights reserved.

Global sales & support: