


SILEX H-260U Print Server for HP EIO



Compatible with


ThinPrint®	TCP/IP	NetBEUI	IPX / SPX		
UNIX / Linux	NetWare	Macintosh	10 / 100 Mbps	AppleTalk	Windows

Experience the technology global printer manufacturers trust

Features & benefits

- The SILEX H-260U is a high performance internal print server** uniquely designed to connect two printers on the network; HP printer with EIO Slots and any other USB printer. It is dual printer support for the price and convenience of one print server.
- The H-260U, a multi-protocol 10/100 TX print server**, is fully compatible with today's network environment. It is ideal for today's businesses from SOHO to large office settings.
- The H-260U is ThinPrint compatible.** Print data is decompressed directly in or at the network printer, which improves bandwidth performance of WAN and LAN systems through the printing process. The much needed bandwidth is available for other essential applications in server-based computing environments such as Windows Terminal Services.
- It is also compatible** with the HP (Web) JetAdmin utility for device control and management.
- The H-260U features leading-edge network capabilities** such as access control using IP Filtering, a high level security feature that prevents unauthorized access to network printers.

Network example



Specifications

Supported OS	Windows 9x, Me, NT 4.0, 2000, XP Sun OS, Solaris, HP-UX, IBM AIX, Linux NetWare 3.x/4.x/5.x/6 (Bindery/NDS) Mac OS 7.6/8.x/9.x, Mac OS X
Supported protocols	TCP/IP: LPD, IPP ¹ , Raw socket #9100 ² , FTP, HTTP, TELNET, SNMP, DDNS, DHCP, BOOTP, RARP, TCP, UDP, ARP, IP, ICMP
	NetWare: IPX, SPX, NDS, Bindery, R/NPRINTER
	AppleTalk: PAP, ATP, ZIP, RTMP, NBP, DDP, AARP, AEP, ELAP
	Windows: NetBEUI, NetBIOS über TCP, WINS
Network interface	10 Base-T / 100 Base-TX (Auto-detection)
Printer interface	HP EIO compliant interface x 1 USB 1.1/2.0 Full-Speed A type x 1 ⁴
Configuration	HP Web JetAdmin compatibility ³ , Quick Setup Utility, Admin Manager Utility, Webbrowser, TELNET
Power consumption	4.0 W (max. 1.25A)
Language	English, German, Chinese, French ⁵
Regulatory approvals	FCC, CE, VCCI Class A
Warranty	2 years
Dimensions	89 x 134 x 32 mm
Weight	90 g
Package contents	SILEX H-260U print server, Quick Setup Guide poster, CD-ROM with configuration utilities and PDF manual

¹ IPP (Internet-Druckprotokoll) Version 1.0.

² For EIO port only.

³ Restriction may apply depending on printer model.

⁴ Caution: Only a USB printer with its own power supply can be connected to the USB port, otherwise the connected printer/device may be damaged.

⁵ German and French are available for Quick Setup Guide poster only.

SILEX TECHNOLOGY is a registered trademark of SILEX TECHNOLOGY, Inc. Other company or product names may be trademarks or registered trademarks of their respective owners. Technical information and specifications are subject to change without notice. © 2008 SILEX TECHNOLOGY Europe GmbH. All rights reserved.

Global sales & support: