

*DESCRIPTION: Single Phase A.C. Input, Variable D.C. Output Control*  
*APPLICATION: Inductive or Resistive D.C. Loads*

Model Number	Fuse Amps	Open Chassis Dimensions Inches			List Price
		Height	Width	Depth	
<b>SINGLE PHASE, 120 VAC INPUT, 0-107 VDC OUTPUT, 50/60Hz</b>					
36TBP-1-5	5	3.25	2.65	3.4	100.00
36TBP-1-10	10	3.33	4.5	3.1	107.00
<b>SINGLE PHASE, 240 VAC INPUT, 0-215 VDC OUTPUT, 50/60Hz (ALSO FOR 208/220/230 VAC INPUT)</b>					
36TBP-2-5	5	3.25	2.65	3.4	118.00
36TBP-2-10	10	3.33	4.5	3.1	140.00

**NOTES:**

1. Model 36TBP controls designed for through-the-door mounting. (See Fig. 1)
  2. All 36TBP controls have factory tested and approved 2-millisecond fuses installed.
  3. For higher voltage or amperage ratings, or for control features not shown here, refer to Model 36D, page 32.
  4. For recommended spare fuses, see FUSE CHART, page 39. Use of any other fuse voids all warranties.
  5. Enclosures supplied by others must be properly ventilated. See VENT SCHEDULE, page 43.
- List prices may be subject to trade classification discounts. Contact your local Payne Engineering Authorized Distributor or representative.

Prices shown are subject to change without notice.



Fig. 1 Model 36TBP 5 AMP



Fig. 1 Model 36TBP 10 AMP

 [Return to Product List](#)