



DESCRIPTION

The FLEXPOWER FP0150-2B100E1 is a multivoltage power supply-battery charger specifically designed for the lifesafety industry. Capable of providing three voltages and charging a standby battery set, the unit is configured in a painted, steel, locking enclosure with tamper switch and integral battery space.

Typically used to provide standby power capability to IT equipment such as modems, routers, or other similar equipment.

Each B100 is capable of providing any power limited voltage between 5 and 18 VDC when used with an FPO power supply. Only one battery set is required to backup all three DC voltages.

BENEFITS

- Agency Listed for Access Control, Fire, Security, CCTV, and Mass Notification
- **FlexPower®** Feature Set
 - ◆ **SureCharge** Microprocessor controlled battery charging
 - ◆ **PowerCom** Power supply programming / monitoring software
 - ◆ **VSelect** Installer selectable output voltage
 - ◆ **TruWatt** Delivers twice the current at 12V than at 24V
 - ◆ **PwrHealth** Intelligent battery charging and battery state monitoring
 - ◆ **FlexConnect** Dual voltage bus / pre-wired accessory board interconnects
 - ◆ **Reliability+** Full fault protection / high efficiency / fiberglass pcb
 - ◆ **GreenSmart** RoHS compliant, lead free, energy efficient design
 - ◆ **DataLink** Network communication interface option

System Features

- ◆ Fully modular power management system
- ◆ Multiple outputs for system power, direct lock control and accessory power distribution modules
- ◆ Fire alarm interface for egress lock control (FAI)
- ◆ Configurable fail-safe / fail-secure modes of operation
- ◆ Comprehensive fault detection and reporting including optional earth ground and battery presence
- ◆ AC and System fault output relays can be delayed via PowerCom
- ◆ Microprocessor dual rate charging restores battery sets from 4 to 80 amhours
- **Power Management & Reporting** (U.S. Patent 8,566,651)
 - ◆ PowerCom® s/w monitors, programs, and reports on power supply core functions through a computer USB or network connection
 - ◆ Service personnel can perform onsite power supply programming and system diagnostics using the DL1 USB cable and a computer laptop
 - ◆ NetLink module option connects power system to a LAN/WAN network for remote programming and live diagnostics. NetLink monitors and reports power status, tests battery state and alerts via email/SNMP on system faults, AC loss, low battery or pre-scheduled service due

Lifetime Warranty

AGENCY LISTINGS

USA		CANADA
UL 294	UL 1481	ULC S318
UL 603	UL 2044	ULC S319
UL 864	UL 2572	ULC S527
UL 1076		CSA C22.2 #107.1
FCC Part 15, Subpart B		CSA 22.2 #60950
CSFM Approved		

ELECTRICAL RATINGS

Parameter	Rating		Unit
	FP0150	B100	
Input Voltage	120 / 230	–	VAC
Input Power (max)	170	–	Watts
Output Voltage	24	5 - 18	VDC
Output Current	4	4 max	Amps
Battery Charge Capacity	80	–	Ah
Efficiency	87	91	%
Output Ripple	120	82	mVp-p
Line Regulation	0.1	0.1	±%
Load Regulation	2	.56	±%
BTU Rating	66	10	BTU/Hr
Continuous Power Outputs	1	1	
Switched Power Outputs	1	No	
Fire Alarm Interface	Yes	No	

FLEXPOWER® STANDARD FEATURES

SureCharge The microprocessor controlled charging process used by the FlexPower power supply guarantees both proper charging current for the battery and fastest charge time. The constant current charger provides a linear, predictable charge time for any lead acid, gel battery set from 4 to 80 amphotours (based on charger rating) without stress or damage to the battery.

PowerCom/PowerCom-USB LifeSafety Power's proprietary software interface for communication with FlexPower equipment through a DATALINK or USB connection. PowerCom is used for power supply monitoring, programming, and reporting.

The NL1 DATALINK network module enhances PowerCom's capability with remote diagnostics, battery management, trouble / service email alerts via LAN/WAN, and remote on/off reset control.

The DL1 USB cable and a computer laptop USB connection, enables PowerCom-USB to be used by service personnel for onsite power supply programming and system diagnostic evaluation.

VSelect One single switch for configuring the output between 12 and 24VDC eliminates field errors and allows for the reduction and simplification of service inventory by eliminating the necessity of stocking units in each voltage.

TruWatt Output power capability of the power supply remains constant regardless of the output voltage setting. For example, a FlexPower 250 watt supply will provide 10 amps at 24VDC and 20 amps at 12VDC, allowing the same number of locking devices to be used at either the 12 or 24V setting.

FlexConnect The FlexPower series provides a prewired interconnection system between the power supply and accessory boards of the power system that introduces the concept of a dual voltage bus structure throughout all system modules and eliminates intermodule wiring by the field installer.

Field upgrading or expansion is as simple as using common mounting footprints, predrilled mounting holes, snap-in standoffs, and pluggable wires to add additional system capability or capacity when needed, all without restrictive agency listing issues.

Reliability+ All power supplies within the FlexPower system are fully fault protected and feature fiberglass printed circuit boards rather than paper-based to protect the electronics from water and other corrosive elements found in industrial settings. High efficiency power supply design promotes low heat generation leading to a longer service life.

GreenSmart All members of the FlexPower family are RoHs compliant, lead-free, and meet the latest state, federal and European requirements for energy efficiency.

DataLink - Smart Power Management Communication Interface Monitor, program, control, and report key power supply functions by computer or local/wide area network using a browser interface or LifeSafety Power's PowerCom® remote management software.

Power supply network connection requires the optional NL1 network module. Power supply computer connection requires the optional DL1 USB cable.

Model No.	Mechanical Info
FPO150-2B100E1	Size: 14" x 12" x 4.5" Weight: 10 lb.

FlexPower Numbering System



Worldwide Headquarters
LifeSafety Power, Inc.
 750 Tower Road, Unit B
 Mundelein, IL 60060 USA
 PH 888-577-2898
 info@lifesafetypower.com

FAULT DETECTION AND REPORTING

The comprehensive fault detection and reporting mechanism of the FPO series provides for both local and remote fault reporting.

On-board visual indicators are provided to give immediate installer feedback. Independent form C relay contacts are provided to report AC and system fault conditions to remote or auxiliary equipment.

Detected Fault Conditions:

- **AC Power**
 - ◆ AC loss, AC low
- **DC Power and System**
 - ◆ Abnormal or loss of power supply operation
 - ◆ Over current, over temperature condition
 - ◆ DC output high, low
 - ◆ Battery Presence, Earth Ground (user optional)
 - ◆ Reversed battery condition, blown fuse or loss of output voltage on selected accessory boards (detected on the power supply)

FIRE ALARM INTERFACE (FAI)

- **Activation Methods**
 - ◆ DC voltage: 9 to 33VDC, 3 to 15mA
 - ◆ Dry contact NO/NC
- **Latch Enable: NC contact set or switch (typically for Canadian use)**

SECONDARY VOLTAGE POWER SUPPLY (B100)


The B100 provides an additional voltage in a system, either to the B2 buss for use with other accessory boards, or via its own output terminals. The B100's input comes from the B1 buss in the system, allowing the FPO's battery set to back up the B100's output voltage without the need for a second battery set.

Output settings for the B100 include 12V and an adjustable setting of 5 to 18V. Multiple B100s can be added to a system for virtually unlimited voltage combinations.

Output current is rated for 4 Amps and the output is rated Class 2, power limited.

To calibrate system loading when the B100 is used, see **Application Note AN07** for more information (www.lifesafetypower.com)

FPO PERFORMANCE GRAPHS



Important: All information, including illustrations, is believed to be reliable. Users, however, should independently evaluate the suitability of each product for their particular application. LifeSafety Power makes no warranties as to the accuracy or completeness of the information, and disclaims any liability regarding its use. LifeSafety Power's only obligations are those in the LifeSafety Power Standard Terms and Conditions of Sale for this product, and in no case will LifeSafety Power or its distributors be liable for any incidental, indirect, or consequential damages arising from the sale, resale, use, or misuse of the product. Specifications are subject to change without notice. In addition, LifeSafety Power reserves the right to make changes—without notification to Buyer—to processing or materials that do not affect compliance with any applicable specification.