

Data Sheet

Constellation® ES.2

2TB and 3TB Capacity-Optimised Enterprise Hard Drives for Bulk-Data Applications

Key Advantages

- Highest-capacity enterprise drive for demanding data growth¹
- Fifth-generation SAS and SATA drives designed for 24x7 reliability
- SAS-based, end-to-end data integrity and enhanced error correction for accurate data storage
- Best-in-class enhanced rotational vibration tolerance ensures consistent performance
- Improved power and cooling efficiencies with low power consumption and enhanced PowerChoice™ technology
- Multi-drive firmware maximised for enterprise system availability
- Robust performance with dual processor and ramp load technologies
- Self-Encrypting Drive (SED) option (AES-256) cuts IT drive retirement costs while protecting data securely where it lives — on the drive²
- FIPS 140-2 Validated™ drives protect data classed as *Sensitive but Unclassified* and *Protected*^{2,3}

Best-fit Applications

- High-capacity bulk data storage
- Mainstream enterprise external storage arrays (SAN, NAS, DAS)
- Enterprise backup and restore — D2D, virtual tape
- Centralised surveillance
- Cloud storage

¹ Seagate recommends validating your configuration with your HBA/RAID controller manufacturer to ensure full 3TB capacity capabilities.

² Self-Encrypting Drives (SED) and FIPS 140-2 Validated drives are not available in all models or countries; may require TCG-compliant host or controller support.

³ See FIPS 140-2 Level 2 Certificate at <http://csrc.nist.gov/groups/STM/cmvp/documents/140-1/1401val2011.htm#1635>



Constellation® ES.2



2TB and 3TB Capacity-Optimised Enterprise Hard Drives for Bulk-Data Applications

Specifications	6Gb/s SAS		SATA 6Gb/s	
	3TB ^{1,2}	2TB ¹	3TB ^{1,2}	2TB ¹
Standard Model Number	ST33000650SS	ST32000645SS	ST33000650NS	ST32000645NS
SED (AES-256) Model Number	ST33000651SS ³	ST32000646SS ³	ST33000651NS ³	ST32000646NS ³
SED (AES-256) Model Number	ST33000652SS ^{3,4}	ST32000647SS ^{3,4}	ST33000652NS ^{3,4}	ST32000647NS ^{3,4}
Features				
Protection Information	Yes	Yes	—	—
Low Halogen	Yes	Yes	Yes	Yes
Cache, Multi-segmented (MB)	64	64	64	64
Reliability/Data Integrity				
Mean Time Between Failures (MTBF, hours)	1.2 million	1.2 million	1.2 million	1.2 million
Reliability Rating at Full 24x7 Operation (AFR)	0.73%	0.73%	0.73%	0.73%
Non-recoverable Read Errors per Bits Read	1 sector per 10 ¹⁵	1 sector per 10 ¹⁵	1 sector per 10 ¹⁵	1 sector per 10 ¹⁵
Power-On Hours per Year	8,760	8,760	8,760	8,760
Bytes per Sector	512, 520, 528	512, 520, 528	512	512
Limited Warranty (years) ⁵	5	5	5	5
Performance				
Spindle Speed (RPM)	7,200	7,200	7,200	7,200
Interface Access Speed (Gb/s)	6.0, 3.0, 1.5	6.0, 3.0, 1.5	6.0, 3.0, 1.5	6.0, 3.0, 1.5
Max Sustained Transfer Rate (MB/s)	155	155	155	155
Seek Time, Average Read/Write (ms)	8.5/9.5	8.5/9.5	8.5/9.5	8.5/9.5
Average Latency (ms)	4.16	4.16	4.16	4.16
Interface Ports	Dual	Dual	Single	Single
Rotational Vibration @ 1,500Hz (rad/sec ²)	12.5	12.5	12.5	12.5
Power Consumption				
Idling (W)	7.4	7.4	7.7	7.7
Typical Operating, Random Read (W)	11.3	11.3	10.7	10.7
Power Supply Requirements	+12V and +5V	+12V and +5V	+12V and +5V	+12V and +5V
PowerChoice™ Technology	Yes	Yes	Yes	Yes
Environmental				
Temperature, Operating (°C)	5 to 60	5 to 60	5 to 60	5 to 60
Vibration, Non-operating: <5Hz to 500Hz(Gs)	4.9	4.9	4.9	4.9
Shock, Operating, 2ms (Read/Write) (Gs)	70/40	70/40	70/40	70/40
Shock, Non-operating, 1ms and 2ms (Gs)	300	300	300	300
Physical				
Height (in/mm, max) ⁶	1.028/26.11	1.028/26.11	1.028/26.11	1.028/26.11
Width (in/mm, max) ⁶	4.010/101.85	4.010/101.85	4.010/101.85	4.010/101.85
Depth (in/mm, max) ⁶	5.787/147.00	5.787/147.00	5.787/147.00	5.787/147.00
Weight (lb/g)	1.543/700	1.543/700	1.543/700	1.543/700
Carton Unit Quantity	20	20	20	20
Cartons per Pallet	40	40	40	40
Cartons per Layer	8	8	8	8

¹ One gigabyte, or GB, equals one billion bytes; and one terabyte, or TB, equals one trillion bytes when referring to drive capacity.

² Seagate recommends validating your configuration with your HBA/RAID controller manufacturer to ensure full 3TB capacity capabilities.

³ Self-Encrypting Drives (SED) and FIPS 140-2 Validated drives are not available in all models or countries; may require TCG-compliant host or controller support.

⁴ See FIPS 140-2 Level 2 Certificate at <http://csrc.nist.gov/groups/STM/cmvp/documents/140-1/1401val2011.htm#1635>

⁵ Nearline products shipped between 31 December 2011 and 30 June 2012 have a 3-year limited warranty. Nearline products shipped before 31 December 2011 or after 30 June 2012 have a 5-year limited warranty.

⁶ These base deck dimensions conform to the Small Form Factor Standard (SFF-8201) found at www.sffcommittee.org.

For connector-related dimensions, see SFF-8223.



www.seagate.com

AMERICAS
ASIA/PACIFIC
EUROPE, MIDDLE EAST AND AFRICA

Seagate Technology LLC 10200 South De Anza Boulevard, Cupertino, California 95014, United States, +1 408 658 1000
Seagate Singapore International Headquarters Pte. Ltd. 7000 Ang Mo Kio Avenue 5, Singapore 569877, +65 6485 3888
Seagate Technology SAS 16-18, rue du Dôme, 92100 Boulogne-Billancourt, France, +33 1 41 86 10 00

© 2012 Seagate Technology LLC. All rights reserved. Printed in USA. Seagate, Seagate Technology and the Wave logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. Constellation, PowerChoice and the Think Green logo are either trademarks or registered trademarks of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. The FIPS logo is a certification mark of NIST, which does not imply product endorsement by NIST, nor by the US or Canadian governments. All other trademarks or registered trademarks are the property of their respective owners. When referring to drive capacity, one gigabyte, or GB, equals one billion bytes; and one terabyte, or TB, equals one trillion bytes. Your computer operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Actual data rates may vary depending on operating environment and other factors. Seagate reserves the right to change, without notice, product offerings or specifications. DS1725.5-1207GB, July 2012