

Data Sheet

Savvio® 10K.5

The optimal balance of capacity, performance and power in a 10K, 2.5 inch enterprise drive

Key Advantages

- Improves storage efficiency with 50% increase in capacity and 18% increase in sustained data rate performance over previous generation
- Delivers the highest-capacity 2.5 inch, 10K RPM hard drive (up to 900 GB) to manage more data without increasing the number of drives
- First SFF drive platform to offer four capacity points on a single platform
- PowerChoice™ technology for T10-compliant power management enables IT organisations to tailor systems for performance and power consumption
- Reduces system design, qualification and inventory costs for OEMs
- Protection Information (PI) protects against inadvertent data change¹
- Self-Encrypting Drive (SED) option (AES-256) cuts IT drive retirement costs while protecting data securely where it lives — on the drive²
- FIPS 140-2 Validated™ Drives protect data classed as *Sensitive but Unclassified* and *Protected*.^{2,3}
- Seagate Unified Storage architecture reduces complexity and cost.

Best-fit Applications

- Mission-critical servers and external storage arrays
- Power- and space-constrained data centres
- Compliance or data security initiatives

¹ The Protection Information (PI) feature requires PI-compliant host or controller support.

² Self-Encrypting Drives (SED) and FIPS 140-2 Validated drives are not available in all models or countries. May require TCG-compliant host or controller support.

³ See FIPS 140-2 Level 2 Certificate at <http://csrc.nist.gov/groups/STM/cmvp/documents/140-1/1401val2011.htm#1635>



Savvio® 10K.5



The optimal balance of capacity, performance and power in a 10K, 2.5 inch enterprise drive

Improves Storage Efficiency

The Savvio® 10K.5 drive is the highest-capacity 2.5 inch, 10K drive and the first drive to offer four capacity points on a single SFF platform. This drive enables OEMs, system builders and end users to improve storage efficiency by providing up to 900 GB in a single drive, helping data centres manage more data without increasing the number of drives, all while increasing sustained data rates by 18% (over previous generation) and maintaining favourable power consumption rates. The small form factor allows enterprises to solve space constraints through higher-density storage.

Seagate PowerChoice™ technology enables OEMs and data centre managers to tailor systems for performance and power consumption, enabling green IT initiatives.

Reduces Cost and Complexity

The Savvio 10K.5 drive reduces system complexity by standardising on a common form factor, storage interface and encryption technology. This means fewer device types, form factors, interfaces and security technologies need to be deployed, inventoried and managed.

Enables Smoother Transitions

OEMs and data centre managers have the flexibility to maintain or upgrade capacity, transition from 3.5 to 2.5 inch form factors, and/or migrate from Fibre Channel to SAS drives in one or more steps. With four capacity points on the same drive platform, the Savvio 10K.5 drive enables easier support for current systems and optimised return on existing investments.

Protects Data

Protection Information and Self-Encrypting Drive options protect data from corruption during the storage process and from exposure should the device be lost, stolen or retired, thus helping organisations to meet compliance and data security objectives. Seagate Instant Secure Erase makes drive retirement and repurposing safe, fast and affordable.

www.seagate.com

Specifications	900GB ¹	600GB ¹	450GB ¹	300GB ¹
SAS Model Number	ST9900805SS	ST9600205SS	ST9450405SS	ST9300605SS
SED Model Number	ST9900705SS ²	ST9600105SS ²	ST9450305SS ²	ST9300505SS ²
SED FIPS 140-2 SAS Model Number	ST9900605SS ^{2,3}	ST9600005SS ^{2,3}	ST9450205SS ^{2,3}	ST9300405SS ^{2,3}
FC Model Number	ST9900805FC	ST9600205FC	ST9450405FC	ST9300605FC
Capacity				
Formatted 512 Bytes/Sector (GB)	900	600	450	300
External Transfer Rate (MB/s) 6 Gb/s Serial Attached SCSI 4Gb/s Fibre Channel	600 400	600 400	600 400	600 400
Performance				
Spindle Speed (RPM)	10K	10K	10K	10K
Average Latency (ms)	3.0	3.0	3.0	3.0
Seek Time Average Read/Write (ms) Track-to-Track Read/Write (ms)	3.7/4.1 0.2/0.4	3.4/3.8 0.2/0.4	3.4/3.8 0.2/0.4	3.4/3.8 0.2/0.4
Sustained Transfer Rate Outer to Inner Diameter (MB/s) Cache, Multi-segmented (MB)	168 to 93 64	168 to 93 64	168 to 93 64	168 to 93 64
Configuration/Reliability				
Discs	3	2	2	1
Heads	6	4	3	2
Non-recoverable Read Errors per Bits Read	1 per 10 ¹⁶	1 per 10 ¹⁶	1 per 10 ¹⁶	1 per 10 ¹⁶
Annualised Failure Rate (AFR)	0.44%	0.44%	0.44%	0.44%
Power Management				
Typical Op (A) +5V/+12V	0.46/0.48	0.46/0.45	0.48/0.46	0.46/0.43
Power Idling (W)	4.4	3.8	3.8	3.5
Environmental				
Temperature, Operating (°C)	5 to 55	5 to 55	5 to 55	5 to 55
Temperature, Non-operating (°C)	-40 to 70	-40 to 70	-40 to 70	-40 to 70
Shock, Operating: 11ms (Gs)	40	40	40	40
Shock, Non-operating, 2ms (Gs)	400	400	400	400
Acoustics Idling (bels — sound power)	3.0	3.0	3.0	3.0
Vibration, Operating: <500Hz (Gs)	0.5	0.5	0.5	0.5
Vibration, Non-operating: <500Hz (Gs)	3.0	3.0	3.0	3.0
Physical				
Height (in/mm, max) ⁴	0.591/15.00	0.591/15.00	0.591/15.00	0.591/15.00
Width (in/mm, max) ⁴	2.760/70.10	2.760/70.10	2.760/70.10	2.760/70.10
Depth (in/mm, max) ⁴	3.955/100.45	3.955/100.45	3.955/100.45	3.955/100.45
Weight (lb/kg)	0.451/0.205	0.475/0.215	0.477/0.216	0.465/0.211
Carton Unit Quantity	30	30	30	30
Cartons per Pallet	50	50	50	50
Cartons per Layer	10	10	10	10
Warranty				
Limited Warranty (years)	5	5	5	5

¹ One gigabyte, or GB, equals one billion bytes; and one terabyte, or TB, equals one trillion bytes when referring to drive capacity.

² Self-Encrypting Drives (SED) and FIPS 140-2 Validated drives are not available in all models or countries. May require TCG-compliant host or controller support.

³ See FIPS 140-2 Level 2 Certificate at <http://csrc.nist.gov/groups/STM/cmvp/documents/140-1/1401val2011.htm#1635>

⁴ These base deck dimensions conform to the Small Form Factor Standard (SFF-8201) found at www.sffcommittee.org. For connector-related dimensions, see SFF-8223.



AMERICAS
ASIA/PACIFIC
EUROPE, MIDDLE EAST AND AFRICA

Seagate Technology LLC 10200 South De Anza Boulevard, Cupertino, California 95014, United States, +1 408 658 1000
Seagate Singapore International Headquarters Pte. Ltd. 7000 Ang Mo Kio Avenue 5, Singapore 569877, +65 6485 3888
Seagate Technology SAS 16-18 rue du Dôme, 92100 Boulogne-Billancourt, France, +33 1 41 86 10 00

© 2012 Seagate Technology LLC. All rights reserved. Printed in USA. Seagate, Seagate Technology and the Wave logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. PowerChoice, Savvio, Seagate Secure and the Unified Storage architecture logo are either trademarks or registered trademarks of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. The FIPS logo is a certification mark of NIST, which does not imply product endorsement by NIST, nor by the US or Canadian governments. All other trademarks or registered trademarks are the property of their respective owners. When referring to drive capacity, one gigabyte, or GB, equals one billion bytes; and one terabyte, or TB, equals one trillion bytes. Your computer operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Actual data rates may vary depending on operating environment and other factors. The export or re-export of hardware or software containing encryption may be regulated by the US Department of Commerce, Bureau of Industry and Security (for more information, visit www.bis.doc.gov), and controlled for import and use outside the USA. Seagate reserves the right to change, without notice, product offerings or specifications. DS1727.4-1201GB, January 2012