

BLS6G2731-6G

LDMOS S-Band radar power transistor

Rev. 01 — 19 February 2009

Product data sheet

1. Product profile

1.1 General description

6 W LDMOS power transistor intended for radar applications in the 2.7 GHz to 3.1 GHz range.

Table 1. Typical performance

Typical RF performance at $T_{case} = 25\text{ }^{\circ}\text{C}$; $t_p = 100\text{ }\mu\text{s}$; $\delta = 10\text{ }\%$; $I_{DQ} = 25\text{ mA}$; in a class-AB production test circuit.

Mode of operation	f (GHz)	V _{DS} (V)	P _L (W)	G _p (dB)	η_D (%)	t _r (ns)	t _f (ns)
pulsed RF	2.7 to 3.1	32	6	15	33	20	10

CAUTION



This device is sensitive to ElectroStatic Discharge (ESD). Therefore care should be taken during transport and handling.

1.2 Features



- Typical pulsed RF performance at a frequency of 2.7 GHz to 3.1 GHz, a supply voltage of 32 V, an I_{DQ} of 25 mA, a t_p of 100 μs and a δ of 10 %:
 - ◆ Output power = 6 W
 - ◆ Power gain = 15 dB
 - ◆ Efficiency = 33 %
- Integrated ESD protection
- High flexibility with respect to pulse formats
- Excellent ruggedness
- High efficiency
- Excellent thermal stability
- Designed for broadband operation (2.7 GHz to 3.1 GHz)
- Internally matched for ease of use
- Compliant to Directive 2002/95/EC, regarding restriction of hazardous substances (RoHS)

1.3 Applications

- S-Band power amplifiers for radar applications in the 2.7 GHz to 3.1 GHz frequency range

2. Pinning information

Table 2. Pinning

Pin	Description	Simplified outline	Graphic symbol
1	drain		
2	gate		
3	source		

[1] Connected to flange.

3. Ordering information

Table 3. Ordering information

Type number	Package		
	Name	Description	Version
BLS6G2731-6G	-	eared flanged ceramic package; 2 mounting holes; 2 leads	SOT975C

4. Limiting values

Table 4. Limiting values

In accordance with the Absolute Maximum Rating System (IEC 60134).

Symbol	Parameter	Min	Max	Unit
V_{DS}	drain-source voltage	-	60	V
V_{GS}	gate-source voltage	-0.5	+13	V
I_D	drain current	-	3.5	A
T_{stg}	storage temperature	-65	+150	°C
T_j	junction temperature	-	200	°C

5. Thermal characteristics

Table 5. Thermal characteristics

Symbol	Parameter	Conditions	Typ	Unit
$R_{th(j-case)}$	thermal resistance from junction to case	$T_{case} = 80\text{ °C}; P_L = 6\text{ W}$		
		$t_p = 100\text{ }\mu\text{s}; \delta = 10\text{ %}$	1.56	K/W
		$t_p = 200\text{ }\mu\text{s}; \delta = 10\text{ %}$	1.95	K/W
		$t_p = 300\text{ }\mu\text{s}; \delta = 10\text{ %}$	2.20	K/W
		$t_p = 100\text{ }\mu\text{s}; \delta = 20\text{ %}$	2.00	K/W

6. Characteristics

Table 6. Characteristics

$T_j = 25\text{ }^{\circ}\text{C}$ unless otherwise specified.

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
$V_{(BR)DSS}$	drain-source breakdown voltage	$V_{GS} = 0\text{ V}; I_D = 0.18\text{ mA}$	60	-	-	V
$V_{GS(th)}$	gate-source threshold voltage	$V_{DS} = 10\text{ V}; I_D = 18\text{ mA}$	1.4	1.8	2.4	V
I_{DSS}	drain leakage current	$V_{GS} = 0\text{ V}; V_{DS} = 28\text{ V}$	-	-	1.4	μA
I_{DSX}	drain cut-off current	$V_{GS} = V_{GS(th)} + 3.75\text{ V}; V_{DS} = 10\text{ V}$	2.7	-	-	A
I_{GSS}	gate leakage current	$V_{GS} = 11\text{ V}; V_{DS} = 0\text{ V}$	-	-	140	nA
g_{fs}	forward transconductance	$V_{DS} = 10\text{ V}; I_D = 0.9\text{ A}$	0.81	-	-	S
$R_{DS(on)}$	drain-source on-state resistance	$V_{GS} = V_{GS(th)} + 3.75\text{ V}; I_D = 0.63\text{ A}$	328	-	1260	$\text{m}\Omega$

7. Application information

Table 7. Application information

Mode of operation: pulsed RF; $t_p = 100\text{ }\mu\text{s}$; $\delta = 10\%$; RF performance at $V_{DS} = 32\text{ V}$; $I_{Dq} = 25\text{ mA}$; $T_{case} = 25\text{ }^{\circ}\text{C}$; unless otherwise specified, in a class-AB production circuit.

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
V_{CC}	supply voltage	$P_L = 6\text{ W}$	-	-	32	V
G_p	power gain	$P_L = 6\text{ W}$	14	15	-	dB
η_D	drain efficiency	$P_L = 6\text{ W}$	30	33	-	%
t_r	rise time	$P_L = 6\text{ W}$	-	20	50	ns
t_f	fall time	$P_L = 6\text{ W}$	-	10	50	ns

Table 8. Typical impedance

f GHz	Z _S Ω	Z _L Ω
2.7	2.44 – j17.78	3.30 – j4.14
2.8	2.99 – j16.04	4.52 – j3.72
2.9	3.94 – j14.56	5.67 – j4.67
3.0	5.44 – j13.75	4.94 – j6.39
3.1	6.89 – j14.58	3.00 – j6.56





Fig 1. Definition of transistor impedance

7.1 Ruggedness in class-AB operation

The BLS6G2731-6G is capable of withstanding a load mismatch corresponding to $V_{SWR} = 5 : 1$ through all phases under the following conditions: $V_{DS} = 32\text{ V}$; $I_{Dq} = 25\text{ mA}$; $P_L = 6\text{ W}$; $t_p = 100\text{ }\mu\text{s}$; $\delta = 10\text{ }\%$.


7.2 Graphs



$V_{DS} = 32$ V; $I_{DQ} = 25$ mA; $t_p = 300$ μ s; $\delta = 10$ %.

- (1) $f = 2.7$ GHz
- (2) $f = 2.9$ GHz
- (3) $f = 3.1$ GHz


Fig 2. Power gain as a function of load power; typical values



$V_{DS} = 32$ V; $I_{DQ} = 25$ mA; $t_p = 100$ μ s; $\delta = 20$ %.

- (1) $f = 2.7$ GHz
- (2) $f = 2.9$ GHz
- (3) $f = 3.1$ GHz


Fig 3. Power gain as a function of load power; typical values



$V_{DS} = 32$ V; $I_{DQ} = 25$ mA; $t_p = 300$ μ s; $\delta = 10$ %.

- (1) $f = 2.7$ GHz
- (2) $f = 2.9$ GHz
- (3) $f = 3.1$ GHz


Fig 4. Drain efficiency as a function of load power; typical values



$V_{DS} = 32$ V; $I_{DQ} = 25$ mA; $t_p = 100$ μ s; $\delta = 20$ %.

- (1) $f = 2.7$ GHz
- (2) $f = 2.9$ GHz
- (3) $f = 3.1$ GHz


Fig 5. Drain efficiency as a function of load power; typical values



$V_{DS} = 32\text{ V}$; $I_{DQ} = 25\text{ mA}$; $t_p = 300\text{ }\mu\text{s}$; $\delta = 10\text{ }\%$.

- (1) $f = 2.7\text{ GHz}$
- (2) $f = 2.9\text{ GHz}$
- (3) $f = 3.1\text{ GHz}$


Fig 6. Load power as a function of input power; typical values



$V_{DS} = 32\text{ V}$; $I_{DQ} = 25\text{ mA}$; $t_p = 100\text{ }\mu\text{s}$; $\delta = 20\text{ }\%$.


- (1) $f = 2.7\text{ GHz}$
- (2) $f = 2.9\text{ GHz}$
- (3) $f = 3.1\text{ GHz}$

Fig 7. Load power as a function of input power; typical values



$V_{DS} = 32\text{ V}$; $I_{DQ} = 25\text{ mA}$; $t_p = 300\text{ }\mu\text{s}$; $\delta = 10\text{ }\%$.

Fig 8. Power gain and drain efficiency as function of frequency; typical values



$V_{DS} = 32\text{ V}$; $I_{DQ} = 25\text{ mA}$; $t_p = 100\text{ }\mu\text{s}$; $\delta = 20\text{ }\%$.

Fig 9. Power gain and drain efficiency as function of frequency; typical values

8. Test information




Table 9. List of components (see Figure 10)			
Striplines are on a double copper-clad Duroid 6006 Printed-Circuit Board (PCB) with $\epsilon_r = 6.15$ and thickness = 0.64 mm.			
Component	Description	Value	Remarks
C1	multilayer ceramic chip capacitor	20 nF	ATC 200B or equivalent
C2, C9	multilayer ceramic chip capacitor	100 pF	ATC 100B or equivalent
C3	multilayer ceramic chip capacitor	10 μ F; 35 V	AVX TAJD106K035R or equivalent
C4, C8	multilayer ceramic chip capacitor	1 nF	ATC 700A or equivalent
C5, C10, C11	multilayer ceramic chip capacitor	20 pF	ATC 100A or equivalent
C6	multilayer ceramic chip capacitor	2.7 pF	ATC 100A or equivalent
C7	electrolytic capacitor	47 μ F; 63 V	
R1	SMD resistor	56 Ω	
R2	SMD resistor	3.9 Ω	
L1, L2, L3	copper (Cu) strips	-	

9. Package outline

Earless flanged ceramic package; 2 leads
SOT975C




Fig 11. Package outline SOT975C

10. Abbreviations

Table 10. Abbreviations

Acronym	Description
LDMOS	Laterally Diffused Metal-Oxide Semiconductor
RF	Radio Frequency
S-Band	Short wave Band
SMD	Surface Mounted Device
VSWR	Voltage Standing-Wave Ratio

11. Revision history

Table 11. Revision history

Document ID	Release date	Data sheet status	Change notice	Supersedes
BLS6G2731-6G_1	20090219	Product data sheet	-	-

12. Legal information

12.1 Data sheet status

Document status ^{[1][2]}	Product status ^[3]	Definition
Objective [short] data sheet	Development	This document contains data from the objective specification for product development.
Preliminary [short] data sheet	Qualification	This document contains data from the preliminary specification.
Product [short] data sheet	Production	This document contains the product specification.

[1] Please consult the most recently issued document before initiating or completing a design.

[2] The term 'short data sheet' is explained in section "Definitions".

[3] The product status of device(s) described in this document may have changed since this document was published and may differ in case of multiple devices. The latest product status information is available on the Internet at URL <http://www.nxp.com>.

12.2 Definitions

Draft — The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. NXP Semiconductors does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

Short data sheet — A short data sheet is an extract from a full data sheet with the same product type number(s) and title. A short data sheet is intended for quick reference only and should not be relied upon to contain detailed and full information. For detailed and full information see the relevant full data sheet, which is available on request via the local NXP Semiconductors sales office. In case of any inconsistency or conflict with the short data sheet, the full data sheet shall prevail.

12.3 Disclaimers

General — Information in this document is believed to be accurate and reliable. However, NXP Semiconductors does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information.

Right to make changes — NXP Semiconductors reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

Suitability for use — NXP Semiconductors products are not designed, authorized or warranted to be suitable for use in medical, military, aircraft, space or life support equipment, nor in applications where failure or

malfunction of an NXP Semiconductors product can reasonably be expected to result in personal injury, death or severe property or environmental damage. NXP Semiconductors accepts no liability for inclusion and/or use of NXP Semiconductors products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

Applications — Applications that are described herein for any of these products are for illustrative purposes only. NXP Semiconductors makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Limiting values — Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) may cause permanent damage to the device. Limiting values are stress ratings only and operation of the device at these or any other conditions above those given in the Characteristics sections of this document is not implied. Exposure to limiting values for extended periods may affect device reliability.

Terms and conditions of sale — NXP Semiconductors products are sold subject to the general terms and conditions of commercial sale, as published at <http://www.nxp.com/profile/terms>, including those pertaining to warranty, intellectual property rights infringement and limitation of liability, unless explicitly otherwise agreed to in writing by NXP Semiconductors. In case of any inconsistency or conflict between information in this document and such terms and conditions, the latter will prevail.

No offer to sell or license — Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.

12.4 Trademarks

Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners.

13. Contact information

For more information, please visit: <http://www.nxp.com>

For sales office addresses, please send an email to: salesaddresses@nxp.com

14. Contents

1 Product profile 1

1.1 General description. 1

1.2 Features 1

1.3 Applications 1

2 Pinning information. 2

3 Ordering information. 2

4 Limiting values. 2

5 Thermal characteristics. 2

6 Characteristics. 3

7 Application information. 3

7.1 Ruggedness in class-AB operation. 4

7.2 Graphs 5

8 Test information. 7

9 Package outline 8

10 Abbreviations. 9

11 Revision history. 9

12 Legal information. 10

12.1 Data sheet status 10

12.2 Definitions 10

12.3 Disclaimers. 10

12.4 Trademarks. 10

13 Contact information. 10

14 Contents 11



Please be aware that important notices concerning this document and the product(s) described herein, have been included in section 'Legal information'.