



STANDARD SERIES

MAIDA STYLE NUMBER D6694ZOV301RA300

MAIDA ITEM NUMBER 01-1122

VARISTOR SPEC SHEET

Electrical Specifications

Continuous AC Voltage	300	VAC
Continuous DC Voltage	390	VDC
Maximum DC Leakage @ 390 VDC	200	uA
Low Varistor Voltage Limit	425	VDC
High Varistor Voltage Limit	518	VDC
Nominal Varistor Voltage	472	VDC
Current for Varistor Voltage	1	mA
Maximum Clamp Voltage	790	V
Maximum Clamp Voltage Test Current	100	A
Peak Current Rating (1 Pulse)	13000	A
Peak Current Rating (2 Pulse)	9000	A
Energy Rating (8X20us)	360	J
Energy Rating (10X1000us)	360	J
Typical Capacitance	1750	pF
Impulse Response Time	< 50	ns
Minimum Hipot of Coating	2500	VDC
Minimum I.R. of Coating	1000	MΩ
Current/Energy Derating Above 85°C	-2.5	%/°C

Thermal Specifications

Minimum Operating Temperature	-40	°C
Maximum Operating Temperature	85	°C
Varistor Voltage Temperature Coeff	-0.05	%/°C
Minimum Storage Temperature	-50	°C
Maximum Storage Temperature	125	°C
Recommended Solder Temperature	260	°C
Recommended Reflow Temperature	260	°C

Notes

Physical Specifications

Lead Style	243F4
X Nominal	0.5 in.
X Tolerance	0.04 in.
Y Nominal	0.155 in.
Y Tolerance	0.03 in.
Z Nominal	0.523 in.
Z Tolerance	0.04 in.
Lead Length Nominal	1.00 in.
Lead Length Tolerance	min. in.
d Nominal	0.04 in.
Wire Gauge	18 AWG
Minimum Marking	Z301-300UL
Nominal Disk Size	25 mm
D Maximum	1.1 in.
T Maximum	0.255 in.
H Maximum	1.25 in.
Coating Type	EPOXY



* Contact Maida for a more detailed configuration drawing.

Safety Agency Recognitions

UL 1449 File Number	E321173
- Tested to Type:	2
C-UL File Number	
CSA File Number	LR33468
VDE File Number	
SEV File Number	



MAIDA DEVELOPMENT COMPANY

P.O. Box 3529

Hampton, Virginia 23663

www.maida.com

Ph: (757) 723-0785 Fax (757) 722-1194