



# LOW PROFILE SERIES

MAIDA STYLE NUMBER R65ZOV551RA510

MAIDA ITEM NUMBER 01-1342

**VARISTOR SPEC SHEET**

### Electrical Specifications

Continuous AC Voltage	550	VAC
Continuous DC Voltage	700	VDC
Maximum DC Leakage @ 700 VDC	200	uA
Low Varistor Voltage Limit	778	VDC
High Varistor Voltage Limit	950	VDC
Nominal Varistor Voltage	864	VDC
Current for Varistor Voltage	1	mA
Maximum Clamp Voltage	1360	V
Maximum Clamp Voltage Test Current	100	A
Peak Current Rating (1 Pulse)	10000	A
Peak Current Rating (2 Pulse)	7000	A
Energy Rating (8X20us)	510	J
Energy Rating (10X1000us)	510	J
Typical Capacitance	410	pF
Impulse Response Time	< 50	ns
Minimum Hipot of Coating	2500	VDC
Minimum I.R. of Coating	1000	MΩ
Current/Energy Derating Above 85°C	-2.5	%/°C

### Thermal Specifications

Minimum Operating Temperature	-40	°C
Maximum Operating Temperature	85	°C
Varistor Voltage Temperature Coeff	-0.05	%/°C
Minimum Storage Temperature	-50	°C
Maximum Storage Temperature	125	°C
Recommended Solder Temperature	260	°C
Recommended Reflow Temperature	260	°C

### Notes

### Physical Specifications

Lead Style	082J1
X Nominal	0.3 in.
X Tolerance	0.04 in.
Y Nominal	0.214 in.
Y Tolerance	0.03 in.
Z Nominal	0.368 in.
Z Tolerance	0.04 in.
Lead Length Nominal	1.00 in.
Lead Length Tolerance	min. in.
d Nominal	0.032 in.
Wire Gauge	20 AWG
Minimum Marking	R65-551UL
Nominal Disk Size	17 mm
D Maximum	0.763 in.
T Maximum	0.373 in.
H Maximum	0.888 in.
Coating Type	EPOXY



\* Contact Maida for a more detailed configuration drawing.

### Safety Agency Recognitions

UL 1449 File Number	E321173
- Tested to Type:	2
CSA File Number	LR33468
VDE File Number	
SEV File Number	



MAIDA DEVELOPMENT COMPANY

P.O. Box 3529

Hampton, Virginia 23663

www.maida.com

Ph: (757) 723-0785 Fax (757) 722-1194