



Date: 07/20/2010

# HC SERIES

MAIDA STYLE NUMBER R65ZOV271HC

MAIDA ITEM NUMBER 01-1932

# VARISTOR SPEC SHEET

### Electrical Specifications

|                                    |       |      |
|------------------------------------|-------|------|
| Continuous AC Voltage              | 270   | VAC  |
| Continuous DC Voltage              | 360   | VDC  |
| Maximum DC Leakage @ 360 VDC       | 200   | uA   |
| Low Varistor Voltage Limit         | 382   | VDC  |
| High Varistor Voltage Limit        | 466   | VDC  |
| Nominal Varistor Voltage           | 434   | VDC  |
| Current for Varistor Voltage       | 1     | mA   |
| Maximum Clamp Voltage              | 710   | V    |
| Maximum Clamp Voltage Test Current | 100   | A    |
| Peak Current Rating (1 Pulse)      | 15000 | A    |
| Peak Current Rating (2 Pulse)      | 12000 | A    |
| Energy Rating (8X20us)             | 325   | J    |
| Energy Rating (10X1000us)          | 325   | J    |
| Typical Capacitance                | 880   | pF   |
| Impulse Response Time              | < 50  | ns   |
| Minimum Hipot of Coating           | 2500  | VDC  |
| Minimum I.R. of Coating            | 1000  | MΩ   |
| Current/Energy Derating Above 85°C | -2.5  | %/°C |


### Thermal Specifications

|                                    |       |      |
|------------------------------------|-------|------|
| Minimum Operating Temperature      | -40   | °C   |
| Maximum Operating Temperature      | 85    | °C   |
| Varistor Voltage Temperature Coeff | -0.05 | %/°C |
| Minimum Storage Temperature        | -50   | °C   |
| Maximum Storage Temperature        | 125   | °C   |
| Recommended Solder Temperature     | 260   | °C   |
| Recommended Reflow Temperature     | 260   | °C   |

### Notes

### Physical Specifications

|                       |           |
|-----------------------|-----------|
| Lead Style            | 082J1     |
| X Nominal             | 0.3 in.   |
| X Tolerance           | 0.04 in.  |
| Y Nominal             | 0.185 in. |
| Y Tolerance           | 0.03 in.  |
| Z Nominal             | 0.352 in. |
| Z Tolerance           | 0.04 in.  |
| Lead Length Nominal   | 1.0 in.   |
| Lead Length Tolerance | min. in.  |
| d Nominal             | 0.032 in. |
| Wire Gauge            | 20 AWG    |
| Minimum Marking       | R65-HZ271 |
| Nominal Disk Size     | 17 mm     |
| D Maximum             | 0.763 in. |
| T Maximum             | 0.336 in. |
| H Maximum             | 0.888 in. |
| Coating Type          | EPOXY     |



\* Contact Maida for a more detailed configuration drawing.

### Safety Agency Recognitions

|                     |         |
|---------------------|---------|
| UL 1449 File Number | E321173 |
| - Tested to Type:   | 2       |
| C-UL File Number    | E321173 |
| CSA File Number     |         |
| VDE File Number     |         |
| SEV File Number     |         |



**MAIDA DEVELOPMENT COMPANY**  
P.O. Box 3529  
Hampton, Virginia 23663  
Ph: (757) 723-0785 Fax (757) 722-1194

www.maida.com