

VARISTOR SPECIFICATION SHEET

Date: 01/20/2009

MAIDA STYLE NUMBER 25FN751K

MAIDA ITEM NUMBER 01-2481

CUSTOMER WEB

CUSTOMER P/N N/A

CONTACT N/A

Electrical Specifications


Continuous AC Voltage	460 VAC
Continuous DC Voltage	615 VDC
Maximum DC Leakage @ 615 VDC	200 uA
Low Varistor Voltage Limit	675 VDC
High Varistor Voltage Limit	825 VDC
Nominal Varistor Voltage	750 VDC
Current for Varistor Voltage	1 mA
Maximum Clamp Voltage	1240 V
Maximum Clamp Voltage Test Current	150 A
Peak Current Rating (1 Pulse)	18000 A
Peak Current Rating (2 Pulse)	12000 A
Energy Rating (8X20us)	630 J
Energy Rating (10X1000us)	630 J
Typical Capacitance	850 pF
Impulse Response Time	< 50 ns
Minimum Hipot of Coating	2500 VDC
Minimum I.R. of Coating	1000 MΩ

Physical Specifications

Lead Style	
X Nominal	0.492 in.
X Tolerance	0.039 in.
Lead Length Nominal	1.00 in.
Lead Length Tolerance	min. in.
Y Nominal	0.307 in.
Y Tolerance	0.03 in.
d Nominal	0.04 in.
Wire Gauge	18 AWG
Minimum Marking	MDC-FV-25N751K
Nominal Disk Size	25 mm
D Maximum	1.142 in.
T Maximum	0.622 in.
H Maximum	1.26 in.

Thermal Specifications

Minimum Operating Temperature	-55 °C
Maximum Operating Temperature	85 °C
Varistor Voltage Temperature Coeff	-0.05 %/°C
Minimum Storage Temperature	-55 °C
Maximum Storage Temperature	125 °C
Current/Energy Derating Above 85°C	-2.5 %/°C

Notes

* Contact Maida for a more detailed configuration drawing.

Safety Agency Recognitions

UL 1449 File Number
 UL 1414 File Number
 CSA File Number
 VDE File Number
 SEV File Number

VARISTOR SPEC SHEET

**DEVELOPMENT COMPANY**

P.O. Box 3529

Hampton, Virginia 23663

(757) 723-0785 Fax (757) 722-1194