

Date: 01/20/2009

MAIDA STYLE NUMBER 20FM112K

MAIDA ITEM NUMBER 01-2371

CUSTOMER WEB

CUSTOMER P/N N/A

CONTACT N/A

Electrical Specifications

Continuous AC Voltage	680	VAC
Continuous DC Voltage	895	VDC
Maximum DC Leakage @ 895 VDC	200	uA
Low Varistor Voltage Limit	990	VDC
High Varistor Voltage Limit	1210	VDC
Nominal Varistor Voltage	1100	VDC
Current for Varistor Voltage	1	mA
Maximum Clamp Voltage	1815	V
Maximum Clamp Voltage Test Current	100	A
Peak Current Rating (1 Pulse)	10000	A
Peak Current Rating (2 Pulse)	6000	A
Energy Rating (8X20us)	610	J
Energy Rating (10X1000us)	610	J
Typical Capacitance	360	pF
Impulse Response Time	< 50	ns
Minimum Hipot of Coating	2500	VDC
Minimum I.R. of Coating	1000	MΩ

Physical Specifications

Lead Style	
X Nominal	0.492 in.
X Tolerance	0.039 in.
Lead Length Nominal	1.00 in.
Lead Length Tolerance	min. in.
Y Nominal	0.394 in.
Y Tolerance	0.03 in.
d Nominal	0.04 in.
Wire Gauge	18 AWG
Minimum Marking	MDC-FV-20M112K
Nominal Disk Size	20 mm
D Maximum	0.945 in.
T Maximum	0.63 in.
H Maximum	1.024 in.

Thermal Specifications

Minimum Operating Temperature	-55	°C
Maximum Operating Temperature	85	°C
Varistor Voltage Temperature Coeff	-0.05	%/°C
Minimum Storage Temperature	-55	°C
Maximum Storage Temperature	125	°C
Current/Energy Derating Above 85°C	-2.5	%/°C

Notes

* Contact Maida for a more detailed configuration drawing.

Safety Agency Recognitions

UL 1449 File Number
 UL 1414 File Number
 CSA File Number
 VDE File Number
 SEV File Number

VARISTOR SPEC SHEET

**DEVELOPMENT COMPANY**

P.O. Box 3529

Hampton, Virginia 23663

(757) 723-0785 Fax (757) 722-1194