PCIe FireWire 1394a Card 2+1 Ports

User Manual

Ver. 1.00

All brand names and trademarks are properties of their Respective owners.

Features and Benefits

- Compliant with PCI Express Base Specification 1.1
- Compliant with IEEE 1394-1995, 1394a-2000 and OHCI 1.1
 Standards
- PCI Express 1-lane(x1) FireWire adapters works with PCI Express slots with different lane width
- Installs in any available PCI Express slot and supports data transfer rates up to 400Mbps
- Provide two external FireWire 400 (1394a) 6-pin ports and one internal FireWire 400 (1394a) 6-pin port – sharing with first external FireWire 400 port
- Support DV camcorders, hard disk, removable drives, scanner, digital cameras and other FireWire audio/video devices
- Onboard power connector to provide reliable power source
- Support Windows® 2000, XP/2003 32/64-bit, Vista 32/64-bit

System Requirements

- Windows® 2000, XP/2003 32/64-bit, Vista 32/64-bit
- PCI Express-enabled system with an available PCI Express slot

MN2000000144 Page 2

Package Contents

- 1 x PCIe FireWire Card 2+1 Ports
- 1 x User's Manual

Optional Accessories

- IEEE 1394a Cable
- Ulead Video Studio CD

Hardware Installation

- 1. Turn Off the power to your computer.
- 2. Unplug the power cord and remove your computer's cover.
- 3. Remove the slot bracket from an available PCIe slot.
- To install the card, carefully align the card's bus connector with the selected PCIe slot on the motherboard. Push the board down firmly.
- 5. Connect the system power source to the board's power connector.
- 6. Replace the slot bracket's holding screw to secure the card.
- 7. Replace the computer cover and reconnect the power cord.

MN2000000144 Page 3

Driver Installation

Please make sure the board is installed before proceeding with driver installation.

Important: If your system doesn't boot to Windows properly with our card installed, check with your system's manufacturer for the latest system firmware update.

Windows® 2000/XP/Vista

Windows® 2000/XP/2003/Vista will automatically detect and install the correct driver for the FireWire 3-Port PCIe Card.

To Verify Windows Installation

Right click My Computer, then click Manage, click Device Manager. The Device Manager window opens. Scroll to the IEEE 1394 Bus host controllers icon and click on the plus symbol, the VIA OHCI Compliant IEEE 1394 Host Controller should be displayed.