

4-Ports USB 2.0 Pocket Hub

User Manual

Ver. 3.00

**All brand names and trademarks are properties of their
Respective owners.**

Features

- USB 1.1 and 2.0 Compliant
- Fully Backward Compatible with USB 1.1
- Up to 480 Mbps (Megabits-Per-Second) Data Transfer Rate
- 40 Times Faster Than The USB 1.1
- Four Independent, Fully Functional, Downstream Ports
- Hot Swappable Plug-n-Play
- 4 USB Type A Ports
- Supports high-speed (480Mbps), full-speed (12Mbps), and low-speed (1.5Mbps) data transfer modes
- Supports simultaneous operation of multiple high-speed USB 2.0 and USB 1.1 devices
- Hot-swapping feature allows you to attach/detach USB devices without powering your computer off
- Support Windows 2000, XP, Vista and Mac OS X or later version

System Requirements

PC

- Windows® 2000, XP, Vista
- Available USB 2.0 port

Mac

- Mac OS 8.6 or greater. Requires OS X for USB 2.0 support
- Available USB 2.0 port

Package Contents

- 1 x 4-Ports USB 2.0 Pocket Hub
- 1 x User's Manual

Optional Accessories

- Power Adapter (DC 5V)

Hardware Installation

1. Plug the USB 2.0 pocket hub into your computer's Hi-Speed USB 2.0 port.

Important Note: The Hub must be connected to a USB 2.0-compliant host in order to function in high-speed mode (480Mbps data rate). If connected to a USB 1.1-compliant host, the Hub will operate only in low or full-speed mode (15/12Mbps).

2. Upon powering up your computer, the USB 2.0 hub will be recognized by the computer's operating system.
3. Once complete, you are ready to plug all peripheral devices into your new USB 2.0 pocket hub.

Specification

USB Specification	USB 1.1 and USB 2.0 compliant
Transfer Rate	480Mbps
Ports	4 x USB Type A Ports
Power Mode	Self/Bus Powered
Output voltage(per port)	+5V DC
Output current(per port)	500mA (max.)
Operating Temperature	5~40 °C
Storage Temperature	-20-60 °C
Humidity	0~80% RH