

High Speed USB 2.0 4-Port Hub

User Manual

Ver. 3.00

**All brand names and trademarks are properties of their
Respective owners.**

Features

- USB 1.1 and 2.0 Compliant
- Fully Backward Compatible with USB 1.1
- Up to 480 Mbps (Megabits-Per-Second) Data Transfer Rate
- 40 Times Faster Than The USB 1.1
- Four Independent, Fully Functional, Downstream Ports
- Hot Swappable Plug-n-Play
- 4 USB Type A Ports
- Supports high-speed (480Mbps), full-speed (12Mbps), and low-speed (1.5Mbps) data transfer modes
- Supports simultaneous operation of multiple high-speed USB 2.0 and USB 1.1 devices
- Hot-swapping feature allows you to attach/detach USB devices without powering your computer off
- Support Windows 2000, XP, Vista and Mac OS X or later version

System Requirements

PC

- Windows® 2000, XP, Vista
- Available USB 2.0 port

Mac

- Mac OS 8.6 or greater. Requires OS X for USB 2.0 support
- Available USB 2.0 port

Package Contents

- 1 x High Speed USB 2.0 4-Port Hub
- 1 x User's Manual

Optional Accessories

- USB Cable
- Power Adapter (DC 5V)

Hardware Installation

1. Plug the Hi-Speed USB 2.0 Cable (type B end) into the upstream port of the Hi-Speed USB 2.0 Hub.
2. Plug the Hi-Speed USB 2.0 Cable (type A end) into your computer's Hi-Speed USB 2.0 Port.
3. Upon powering up your computer, the USB 2.0 hub will be recognized by the computer's operating system.

4. Once complete, you are ready to plug all peripheral devices into your new Hi-Speed USB 2.0 Hub.

Specification

USB Specification	USB 1.1 and 2.0 compliant
Transfer Rate	480Mbps
Ports	4 downstream, 1 upstream
Power Mode	Self/Bus Powered
Output voltage(per port)	+5V DC
Output current(per port)	500mA (max.)
Operating Temperature	5~40 °C
Storage Temperature	-20-60 °C
Humidity	0~80% RH