





REV.	DATE	DESCRIPTION
NC	01/17/06	INITIAL RELEASE



RECOMMENDED CABLE
STRIPPING DIMENSIONS

NOTE:

1. CRIMPED FERRULE
HEX CRIMP SIZE .255"
2. CONTACT PIN TO SOLDER

					UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN [] ARE IN INCHES AND FOR CUSTOMER REFERENCE ONLY. UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE: 0.5 – 8mm ± 0.20mm 8 – 30mm ± 0.40mm 30 – 120mm ± 0.50mm UNLESS OTHERWISE SPECIFIED TOLERANCES FOR INCHES ARE: .020 – .315 = ± 0.007" .315 – 1.180 = ± 0.015" 1.180 – 4.724 = ± 0.020" DO NOT SCALE DRAWING	APPROVALS	DATE	Amphenol Connex							
8						DRAWN	G.R.S.								01/17/06
7						CHECKED			PART DESCRIPTION MINI 75ohm SMB R/A CRIMP PLUG (FOR RG-59A/U, 59B/U, CABLE)						
6						ISSUED									
5	FERRULE	COPPER	GOLD	1		SHEET	1 OF 1		PART NO. 142336-75						
4	COVER	BRASS	GOLD	1											
3	CONTACT PIN	BER. COPPER	GOLD	1				DWG. NO. 142336-75.DWG							
2	INSULATOR	TEFLON	NATURAL	1											
1	BODY	BRASS	GOLD	1				REV. NC	SIZE A	SCALE NA					
	DESCRIPTION	MATERIAL	FINISH	QTY		CAD FILE	C:/142/142336-75.DWG								