









|                                                                                                                                                      |                                                                                                                                                                     |                                                                                                                                                          |
|------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------|
| <p>Fig. 1</p>  <p>Bead Contact Sub-Assembly<br/><b>131-1052</b></p> | <p>Fig. 2</p>  <p>Bead<br/><b>131-1053</b></p>                                     | <p>Fig. 3</p>  <p>Contact Sub-Assembly<br/><b>131-1054</b></p>        |
| <p>Fig. 4</p>  <p>Body<br/><b>131-122</b></p>                       | <p>Fig. 5</p>  <p>Optimal Fluted Nut<br/><b>131-126</b></p>                        | <p>Fig. 6</p>  <p>Collet<br/><b>131-129</b></p>                       |
| <p>Fig. 7</p>  <p>Retainer Sub-Assembly<br/><b>131-131</b></p>    | <p>Fig. 8</p>  <p>Nut, Body &amp; Assembly Sub-Assembly<br/><b>131-91057</b></p> | <p>Fig. 9</p>  <p>Coupling Nut Standard Hex.<br/><b>131-926</b></p> |

## COMPONENTS AND SUB-ASSEMBLIES

| Description                                                                                 | Dimensions, Inches (mm) |             | Amphenol Number           | Fig. |
|---------------------------------------------------------------------------------------------|-------------------------|-------------|---------------------------|------|
|                                                                                             | a                       | b           |                           |      |
| Bead-contact sub-assembly                                                                   | .461 (11.7)             | .370 (9.4)  | <a href="#">131-1052</a>  | 1    |
| Bead                                                                                        | .116 (3.0)              | .370 (9.4)  | <a href="#">131-1053</a>  | 2    |
| Contact (Collet & Collet holder) sub-assembly                                               | .183 (4.6)              | .120 (3.0)  | <a href="#">131-1054</a>  | 3    |
| Body for 7mm Airline                                                                        | .800 (20.3)             | .576 (14.6) | <a href="#">131-122</a>   | 4    |
| Optional Fluted Coupling Nut                                                                | .702 (17.8)             | .812 (20.6) | <a href="#">131-126</a>   | 5    |
| Collet                                                                                      | .149 (3.8)              | .103 (2.6)  | <a href="#">131-129</a>   | 6    |
| Retainer sub-assembly                                                                       | .676 (17.2)             | .687 (17.5) | <a href="#">131-131</a>   | 7    |
| Coupling Nut — Retainer body sub-assembly for 7mm Airline (131-91051 less bead-contact S/A) | .921 (23.4)             | .865 (22.0) | <a href="#">131-91057</a> | 8    |
| Standard Hex coupling nut                                                                   | .702 (17.8)             | .865 (22.0) | <a href="#">131-926</a>   | 9    |