



REVISIONS				
SYM	ZONE	ECN, ERN NO.	DATE	APPRD.
A		PROPOSAL	JAN.22/13	L.CHAN
B		PROPOSAL	APR15/13	L.CHAN



NOTES:

1. MATERIALS:
 PLASTIC HOUSING: HIGH TEMPERATURE THERMOPLASTIC
 FLAMMABILITY RATING UL 94V-0, COLOR: BLACK



 CONTACTS: PHOSPHOR BRONZE
 PLATING: 15 μ" [0.38 MICRONS]
 MIN. GOLD ON MATING SURFACES.
 50 μ" [1.27 MICRONS]
 MIN. NICKEL UNDERPLATE
 100 μ" [2.54 MICRONS]
 MIN. MATTE TIN ON CONTACT TAILS.

 SHIELD: STAINLESS STEEL WITH TIN DIP ON SOLDER TAIL


 2. RECOMMENDED SOLDERING TEMPERATURE:
 WAVE SOLDERING AT 260°C MAXIMUM FOR 5 SEC MAXIMUM.

3. PART NUMBER: RJHSE-GF8X
 REFER TO LED OPTIONS DRAWING FOR ORDERING CODES

DRAWN	AMY.Z	DATE	JAN22/13	Amphenol Canada Corp.		
DESIGNED						
CHECKED	L.CHAN		JAN22/13			
I. E. APPRD.						
Q. A. APPRD.						
DWG. APPRD.				HIGH SPEED, RJ45, MODULAR JACK, 8 POSITION, 8 CONTACTS, WITH LEDs SHIELDED WITHOUT TABS-RoHS COMPLIANT		
ENG. REL. NO.						
REF.				P-RJHSE-GF8X		
DIMENSIONS ARE IN INCHES [mm]	CODE ID. NO.	03554				
				SCALE	WT. -----	SURF. -----
						SHEET 1 OF 1



RECOMMENDED P.C.B. LAYOUT
(COMPONENT SIDE OF BOARD)



RECOMMENDED PANEL CUTOUT

THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION AND SUCH INFORMATION MAY NOT BE DISCLOSED TO OTHERS FOR ANY PURPOSE OR USED FOR MANUFACTURING PURPOSES WITHOUT WRITTEN PERMISSION FROM AMPHENOL CANADA CORP.

