

SATA Solid State Drive

■ TeraNova SATA III 6Gbps SSD



Targeted at the Pro/Enthusiast seeking extreme performance, the TeraNova is one of several durable 2.5" SSD's that SuperTalent has released to date. Featuring the SATA3 Interface with optimized firmware, the SuperTalent TeraNova is built for reliable speed. By optimizing the transfer rate at various queue depths, the TeraNova delivers excellent performance in a variety of conditions. Sure the TeraNova boots quickly and posts outstanding benchmark scores (over 500MB/s for read and 410MB/s for write), but the TeraNova also excels in general responsiveness.

The TeraNova also includes new features that enhance reliability as well. In the event of a sudden power loss, the TeraNova reacts, protecting valuable data from corruption before it powers off.

Physical Specifications

Form Factor	2.5"
Capacity*	60GB-480GB
Dimension	69.85 x 100.00 x 6.90 mm
SATA Interface	SATA III
NAND Flash	MLC
Power Supply	5V ± 10%
Package	Metal housing

Environmental Specifications

Operating Shock	1500G
Operating Vibration	16G
Operating Temperature	0C to +70C
Operating Humidity	8 to 95% @ 25C

Ordering Information

60GB	FTM06N325H
120GB	FTM12N325H
240GB	FTM24N325H
480GB	FTM48N325H