

**DuraDrive ET3**

**IDE/PATA Solid State Drive**



Super Talent's DuraDrive ET3 displays the next generation of industrial data storage solutions through enhanced durability, reliability and performance environments considered "too harsh" for a standard drive.

Supporting access times of 0.1ms, the DuraDrive can reach read and writes speeds of up to 110/95 MB/sec. With ECC/EDC support, bad bit management firmware and patented wear leveling technology, the DuraDrive ET3 is sure to fit your computing needs.

Featuring the industry standard 2.5" form factor and IDE/PATA interface, the DuraDrive ET3 is 100% interchangeable with conventional 2.5" IDE/PATA hard drives.

This SSD is geared specifically for applications that require high shock, vibration, and/or reliability. Examples include:

- Medical Industry
- Embedded/Industrial Systems
- Enterprise Computing
- Aerospace
- Casino Gaming

**Physical Specifications**

	DuraDrive ET3
Form Factor	2.5"
Capacity	32-256GB(MLC),16-64GB(SLC)
Dimensions	100.2 x 69.85 x 9.5 mm
Interface	IDE/PATA
NAND Flash	MLC/SLC
Power Supply	5V ± 10%
Package	Complete metal housing

**Environmental Specifications**

Shock (Operating)	1500G
Vibration (Operating)	16G
Operating Temperature (Industrial)	-40°C ~ 85°C
Operating Temperature (Commercial)	0°C ~ 70°C

**Ordering information**

MLC	
<b>32 GB</b>	FE8032MD2D
<b>64 GB</b>	FE8064MD2D
<b>128 GB</b>	FE8128MD2D
<b>256 GB</b>	FE8256MD2D

SLC	
<b>16 GB</b>	FEK016MD2D
<b>32 GB</b>	FEK032MD2D
<b>64 GB</b>	FEK064MD2D