



MATERIAL:
HOUSING MATERIAL: GLASS FILLED POLYESTER
FLAMABILITY RATING: UL94-V0
COLOR: RED
MAX TEMP.: 260°C 10s
CONTACT MATERIAL: PHOSPHOR BRONZE
CONTACT TYPE: STAMPED
CONTACT PLATING: MATT TIN OVER NICKEL
QUALITY CLASS: 25 MATING CYCLES
PITCH: 2.54 MM PER ROW
1.27 MM RIBBON CABLE

ENVIRONNEMENTAL:
OPERATING TEMPERATURE: -40°C UP TO 105°C
COMPLIANCE: LEAD FREE AND ROHS

ELECTRICAL:
CURRENT RATING: 1.0 A PER PIN (CABLE)
WORKING VOLTAGE: 100VAC
INSULATION RESISTANCE: >1000MOHM
DIELECTRIC WITHSTANDING VOLT.: 500VAC/MN
CONTACT RESISTANCE: 10mOHM MAX

STANDARD
 c  US CERTIFIED: E323964 / MOD. NUMBER 69015700xx7x

DIMENSION:
DIM.A= 1.27 x No. of Spaces
DIM.B= DIM.A + 3.3
DIM.C= DIM.A + 2.1
DIM.D= DIM.A + 4.7

AVAILABLE
xx : 4 TO 26 CIRCUITS

PACKAGING: TUBE

RoHS Compliant				PROJECTION: 	GENERAL TOLERANCE .X = +/- 0.2 .XX = +/- 0.15			SIZE
G								
F								
E								
D	13-NOV-13	DWG UPDATE	QL	APPROVAL: RJ	UNIT: MM	DESCRIPTION: MM MALE IDC CONNECTOR		A4
C	07-APR-10	PINNING	JP		SCALE:			
B	09-MAR-10	STANDARD	JP		SHEET: 1/1			
A	03-NOV-06	PDF	JP		DRAW: EAGER			
REV	DATE	FILE	BY					