

TECHNICAL CHARACTERISTICS

MATERIAL
 INSULATOR: PBT
 COLOR: BLACK
 CONTACT MATERIAL: COPPER ALLOY
 CONTACT TYPE: STAMPED
 CONTACT PLATING: GOLD
 QUALITY CLASS: 3 AS PER CECC 75 301-802
 PITCH: 2.54MM

ENVIRONMENTAL
 OPERATING TEMPERATURE: -40 UP TO 125°C
 FLAMABILITY RATING: UL94-V0
 COMPLIANCE: LEAD FREE AND ROHS

ELECTRICAL
 CURRENT RATING: 3A MAX
 WORKING VOLTAGE: 250V AC
 INSULATOR RESISTANCE: >1000 MOHM
 DIELECTRIC WITHSTANDING VOLTAGE: 500V AC/MN
 CONTACT RESISTANCE: 20 mOHM MAX

STANDARD
 CERTIFIED: E323964 / MODEL NUMBER 612-217

SOLDERING
 WAVE PROCESS ONLY

PACKAGING
 TRAY

DIMENSION
 A = 2.54 x (NB. PIN / 2 - 1)
 B = 2.54 x (NB. PIN / 2) + 7.66


RoHS Compliant			
G	16-NOV-09	PACKAGING	JC
F	16-NOV-09	STANDARD	JP
E	03-MAR-08	PIN POSITIONS	CH
D	26-DEC-07	PIN POSITIONS	CH
C	19-DEC-06	DRAW	EC
B	21-JUN-04	LEAD FREE	JP
A	09-MAR-99	PDF	JP
REV	DATE	FILE	BY

PROJECTION:	
APPROVAL: RJ	

GENERAL TOLERANCE	.X = +/- 0.2
	.XX = +/- 0.15
UNIT: MM	
SCALE:	
SHEET: 1/2	
DRAW: PEARL	

	DESCRIPTION: 2.54MM MALE ANGLED BOX HEADER
	WERI PART NO: 612 0xx 217 21

SIZE	A4



RoHS Compliant				PROJECTION: 	GENERAL TOLERANCE .X = +/- 0.2 .XX = +/- 0.15	
G						
F				APPROVAL: RJ	UNIT: MM	DESCRIPTION: 2.54MM MALE ANGLED BOX HEADER
E					SCALE:	
D					SHEET: 2/2	WERI PART NO: 612 0xx 217 21
C					DRAW: PEARL	
B						
A						
REV	DATE	FILE	BY			

SIZE
A4