



TECHNICAL CHARACTERISTICS

MATERIAL  
 INSULATOR: PBT  
 FLAMABILITY RATING: UL94-V0  
 COLOR: BLACK  
 CONTACT MATERIAL: COPPER ALLOY  
 CONTACT TYPE: STAMPED  
 CONTACT PLATING: SELECTIVE GOLD  
 SHIELDING: STEEL NICKEL PLATED  
 QUALITY CLASS: 3 AS PER CECC 75 301-802

ENVIRONMENTAL  
 OPERATING TEMPERATURE: -40 UP TO 85°C  
 COMPLIANCE: LEAD FREE AND ROHS

ELECTRICAL  
 CURRENT RATING: 3A  
 WORKING VOLTAGE: 125V AC  
 INSULATOR RESISTANCE: >5000 MOHM  
 DIELECTRIC WITHSTANDING VOLTAGE: 1000V AC/MN  
 CONTACT RESISTANCE: 30 mOHM MAX

STANDARD  
 CERTIFIED E323964

SOLDERING: WAVE PROCESS ONLY

PACKAGING  
 TRAY

ACCESSORIES  
 UNC 4-40 RIVET / BOARD LOCK

DIMENSION

PINS	A	B	C
9	16.92	25.0	30.8
15	25.25	33.3	39.2
25	38.96	47.1	53.1
37	55.42	63.5	69.4

RoHS Compliant	
G	06-JAN-14
F	22-AUG-12
E	23-FEB-12
D	05-AUG-09
C	07-DEC-09
B	19-NOV-09
A	19-NOV-09
REV	DATE

DIM & UL	QL
UL	GG
DRAWING	GG
DIMENSION	GG
WORKING VOLT.	JP
STANDARD	JP
STANDARD	JP
FILE	BY

PROJECTION:

APPROVAL: RJ

GENERAL TOLERANCE  
 X. = +/\_ 0.5  
 .X = +/\_ 0.3  
 .XX = +/\_ 0.2

UNIT: MM  
 SCALE:  
 SHEET: 1/1  
 DRAW: PEARL

DESCRIPTION: D-SUB MALE ANGLED PCB CONNECTOR - 10.3MM WITHOUT SCREW

WERI PART NO: 618 0xx 233 721

SIZE  
**A4**