



TECHNICAL CHARACTERISTICS

MATERIAL
 INSULATOR: PA 66
 FLAMABILITY RATING: UL94-V0
 COLOR: LIGHT GREEN
 CONTACT MATERIAL: BRASS (CuZn)
 PLATING: TIN PLATED

ENVIRONMENTAL
 OPERATING TEMPERATURE: -40 UP TO 105°C
 COMPLIANCE: LEAD FREE AND ROHS

ELECTRICAL
 CURRENT RATING: 10A
 WORKING VOLTAGE: 300VAC
 WITHSTANDING VOLTAGE: 2000 V AC/MN
 INSULATION RESISTANCE: >2000M OHM
 CONTACT RESISTANCE: 20 mOhm MAX

STANDARD
 CERTIFIED E315414 / MODEL NUMBER 357B

SCREW: M2.5
 PITCH: 3.81mm

SOLDERING: WAVE PROCESS ONLY

PACKAGING: BOX

SERIE 357

DIMENSIONS

PINS	A
4	18.21
6	22.02
8	25.83
10	29.64
12	33.45
14	37.26
16	41.07

RoHS Compliant				PROJECTION: 	GENERAL TOLERANCE .X = +/- 0.2 .XX = +/- 0.15		
G							
F							
E							
D				APPROVAL: RJ	UNIT: MM	DESCRIPTION: SERIE 357 - 3.81MM DOUBLE LEVEL HORIZONTAL MALE PCB HEADER WITH FLANGES TYPE WR - TBL	
C					SCALE:		
B	15-MAY-13	UL	JC		SHEET: 1/1		WERI PART NO: 691 357 310 0xxB
A	30-JAN-13	PDF	QL		DRAW: QL		
REV	DATE	FILE	BY			SIZE A4	

A
B
C
D