

## TECHNICAL CHARACTERISTICS

### SPECIFICATION

#### >Contact Rating:

Switching: 150mA, 24VDC  
Non-Switching: 400mA, 24VDC

#### >Contact Resistance:

Initial: 80mOHM max.  
After Life Test: 200mOHM max.

>Insulation Resistance: min. 100MOHM at 250VDC

>Dielectric Strength: 250VAC for 1 minute

>Operating Force: 700g max.

>Life cycle: 10.000 steps

>Position: 10

>Actuator: Shaft type

### MATERIAL

>Cover: PA66 UL 94V-0, color light grey

>Base: PA66 UL 94V-0, color black

>Actuator: POM UL HB

>Contact: Gold Plated

>Terminal: Gold Plated

### SOLDERING INFORMATION

>Terminal in THT version

>Wave soldering 260°C for 10 sec. max

>Hand soldering at 350°C for 3 sec. max

### WASHABLE DEFINITION

Please do not submerge washable products into water or cleaning agents or put them in locations exposed to water or liquids completely. When cleaning by hand (brushing), please do not use excessive force on our switch to avoid malfunction afterwards, because you could deform function relevant areas or you could damage sealing functions. Do not clean washable series immediately after soldering. The cleaning agent may be absorbed into the switch through respiration while the switch cools.

### ENVIRONMENTAL

>Storage condition: -40°C ~ +85°C

>Operation condition: -40°C ~ +85°C

>Compliance: Lead Free, ROHS, Reach

### PACKAGING INFORMATION


#### >Tube

Part number	Color of Actuator	Position	Code
428 527 420 910	dark grey	10	Real Code
428 527 420 911	ivory	10	complement code

10 Position	Real Code							
	C	1	2	4	8	0	1	2
0	•					0		
1		•				1		
2		•		•		2		
3		•	•	•		3		
4		•			•	4		
5		•			•	5		
6		•		•	•	6		
7		•	•	•	•	7		
8		•			•	8		
9		•	•		•	9		

10 Position	Complement Code							
	C	1	2	4	8	0	1	2
0	•	•	•	•	•	0		
1		•				1		
2		•			•	2		
3		•			•	3		
4		•	•	•	•	4		
5		•			•	5		
6		•			•	6		
7		•			•	7		
8		•	•	•	•	8		
9		•	•		•	9		

Scale - 2:1



This electronic component is designed and developed with the intention for use in general electronics equipments.

Before incorporating the components into any equipments in the field such as aerospace, aviation, nuclear control, submarine, transportation, (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc. where higher safety and reliability are especially required or if there is possibility of direct damage or injury to human body, Wurth Elektronik must be asked for a written approval.

In addition, even electronic component in general electronic equipments, when used in electrical circuits that require high safety, reliability functions or performance, the sufficient reliability evaluation-check for the safety must be performed before by the user before usage.

REV	FILE	DATE	BY	EDV NO	System	SIZE
				42852742091x.dft	Solid Edge V20	
a	warning text	11-09-30	WJ			
b	new contact rating	12-02-02	WJ			
c	Washable Definition	14-03-06	DaF	Würth Elektronik eiCan CAD	Drawing.- No. 42852742091x	A4
d	revised MatchCode	14-07-25	AL			