

TECHNICAL CHARACTERISTICS

MATERIAL

>Basic: PC UL HB

MOUNTING INSTRUCTION

>For reflow soldering only to be fitted after the soldering process

PACKAGING INFORMATION

>Tray



P/N	Laser carving sign	Base color
714 401 001	⏻	black
714 401 002	▲	black
714 401 003	◀	black
714 409 0100	no	transparent

Scale - 2:1

This electronic component is designed and developed with the intention for use in general electronics equipments.

Before incorporating the components into any equipments in the field such as aerospace, aviation, nuclear control, submarine, transportation, (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc. where higher safety and reliability are especially required or if there is possibility of direct damage or injury to human body, Wurth Elektronik must be asked for a written approval.

In addition, even electronic component in general electronic equipments, when used in electrical circuits that require high safety, reliability functions or performance, the sufficient reliability evaluation-check for the safety must be performed before by the user before usage.

Projection							GENERAL TOLERANCE .x = +/- 0,2 .xx = +/- 0,15			Basic material		
					Date	Name	DESCRIPTION SwCaps Caps 12x12mm illuminated tact switch WS-TLT					
				Drawn	12-10-15	Jelisarow						
				Checked								
												
							Scale	2:1	Position		SIZE	
							Drawing.- No. 714401xxx				A4	
REV	FILE		DATE	BY	EDV NO	714401xxx.dft	System: Solid Edge ST4					