

**PRODUCT OVERVIEW**

| | |
|-------------------------|------------------------|
| DC Output Voltage | 27.0V (DC) @ FULL LOAD |
| Output Amperage | 15 Amps |
| Input Voltage Range | 108 - 132 AC |
| Input Voltage Frequency | 47-63 Hz |

DESCRIPTION

The **DLS-27-15** battery charger/power converter from IOTA Engineering converts nominal 120V A.C. voltage to 27.2V D.C. As a power supply, its tightly controlled regulation allows the user to operate any appropriate nominal D.C. load up to the converter's rated output current. As a battery charger, the **DLS-27-15** will maintain the battery, delivering its full-rated current when the battery capacity falls sufficiently low. The voltage is set to deliver its maximum current for the necessary period of time that minimizes undue stress to the battery caused by heating of its cells. This helps to ensure the longest possible life of the battery. Over time, as the battery nears its full capacity, the converter will float-charge the battery to prevent self-discharge of its cells.

TECHNICAL SPECIFICATIONS

| | |
|-------------------------------------|--------------------|
| DC Output Voltage (No Load) approx. | 27.2V (DC) |
| Output Voltage Tolerance (No Load) | + or - .5% |
| Output Amperage, Max Continuous | 15 Amps |
| Output Voltage (Full Load) approx. | >27.0V (DC) |
| Maximum Power Output, Continuous | 400 Watts |
| Ripple and Noise | <50 mV rms |
| Input Voltage Range | 108 - 132 AC |
| Input Voltage Frequency | 47-63 |
| Maximum AC Current (@108VAC) | 7.3 Amps |
| Typical Efficiency | >80% |
| Max Inrush Current, Single Cycle | 30 Amps |
| Short Circuit Protection | Yes |
| Overload Protection | >100% |
| Line Regulation | 100 mV rms |
| Load Regulation | <1% |
| Fan Control* | Proportional |
| Thermal Protection | YES |
| Working Temperature Range | 0° - 40° C |
| Storage Temperature | -20° to 80° C |
| Withstand Voltage (VDC)** | 1700/1700/500 |
| Dimensions† | 9.7" x 6.7" x 3.4" |
| Weight | 4.5 lbs |

*Proportional = Fan speed proportional to case temperature.

**Primary to Chassis/Primary to Secondary/Secondary to Chassis

†See reverse side for detailed mounting specifications.

FEATURES

- Switch-mode technology
- Exceptionally clean DC output
- Tight line-load regulation
- Quickly and efficiently charges batteries
- Designed to withstand low transient AC line voltage
- Current limit and thermal/overload protection
- Lower operating temperature
- Proportional fan control circuitry allows fan to start and stop slowly for quiet fan operation
- External reverse polarity fuse protection from incorrect battery connection
- Charging Jack allows for normal and high-stage charging
- Compatible with IOTA IQ Smart Charger for automatic three-stage charging



IOTA
POWERING YOUR WAY

P.O. BOX 11846 TUCSON, AZ 85734
(520) 294-3292 • FAX (520) 741-2837
www.iotaengineering.com

DLS-27-15

BATTERY CHARGER/POWER CONVERTER

OPTIONS


MODELS

- DLS-27-15
- DLS-27-15/IQ4 (with integrated IQ Smart Charger)

DUAL VOLTAGE JACK

The **DLS-27-15** is equipped with a Dual Voltage Jack and Dual Voltage Plug that allows manual switching from a long-term float voltage of 27.2vdc to 28.4vdc. When the Dual Voltage Plug is inserted in the jack, the voltage increases to 28.4vdc for occasional fast charging. When the plug is removed, the voltage drops to 27.2vdc to reduce battery water loss.


The Dual Voltage Jack also allows for easy installation of an external IQ4 Smart Charger for automatic 3-stage charging (optional). If the unit is equipped with an internal IQ4 smart charger, two-step charging is not needed and the Dual Voltage Jack is disabled. For details on 3-stage charging voltages, refer to the IQ4 instruction manual.



INSTALLATION OVERVIEW

Disconnect the positive side of the battery before installation. Connect the positive (red) and negative (black) terminal lugs to battery or load. Always use the proper size wire based on the amperage of the converter and the battery. When connecting to a battery, a breaker should be installed within 18" of the battery, connecting the battery positive to the line side of the breaker, and the DLS to the load side. Connect "Chassis Bonding Lug" on the DLS to vehicle chassis or other grounding source.

Plug the DLS A.C. input cord into a 120 volt 3-wire grounded source. See chart for maximum current draw and required input voltages. For complete installation guidelines, refer to the installation manual.



WARRANTY

The DLS Series Battery Charger/Power Converter is warranted from defects in materials or workmanship for two years from date of retail purchase, and limits the remedies to repair or replacement. This warranty is valid only in the continental United States and Canada. For complete warranty details, contact Customer Service or visit www.iotaengineering.com.

MOUNTING FOOTPRINT

