



Inverter Remote Control

Pure Sine Wave

Model
S-R6-12

Design Features

- Designed for use with 12V versions of SA, SK & ST Series of Pure Sine Wave Inverters with 12 VDC input
- Reverse override function
- 10 feet of connecting cable included
- Bar Meter Monitor for battery voltage and output power
- LED indicators for:
 - Over voltage protection
 - Under voltage protection
 - Over temperature protection
 - Over load protection
 - Power save mode
 - Inverter ON condition
 - Grid pass through condition (ST Series)

2 YEAR WARRANTY

MODEL NO.	S-R6-12		
INPUT VOLTAGE	12V Nominal Battery System Voltage		
STANDBY CURRENT DRAW	< 80 mA		
OPERATING TEMPERATURE RANGE	0°C to 40°C / 32°F to 104°F		
STORAGE TEMPERATURE RANGE	-30°C to 70°C / -22°F to 158°F		
CONNECTING CABLE	- 10 ft, 4 Conductors - 4P4C or 6P4C Modular Plugs - Straight Connection		
DIMENSIONS, INCHES (W x D x H)	5.1 x 1.02 x 4.7		
DIMENSIONS, MM (W x D x H)	130 x 26 x 120		
WEIGHT (WITHOUT CABLE), g	356		
WEIGHT (WITHOUT CABLE), lbs	0.8		
FOR USE WITH SPECIFIC INVERTER MODELS (12V INPUT VERSIONS ONLY)	SA-1000K	SK700	ST-1500
	SA-2000K	SK1000	
	SA-3000K	SK1500	
		SK2000	
		SK3000	

NOTE: Specifications are subject to change without notice

12003-S-R6-12-0413