



Inverter Remote Control

Pure Sine Wave

Model
S-R8

Design Features

- Designed for use with 12V / 24V / 48V versions of SA, SK & ST Series of Pure Sine Wave Inverters
- Push button system ON/OFF
- LED indicators for ON conditions, remote override and ignition lockout
- 10 feet of connecting cable included

2 YEAR WARRANTY

MODEL NO.	S-R8		
INPUT VOLTAGE	12V or 24V or 48V Nominal Battery System Voltage		
STANDBY CURRENT DRAW	< 40 mA		
OPERATING TEMPERATURE RANGE	0°C to 40°C / 32°F to 104°F		
STORAGE TEMPERATURE RANGE)	-30°C to 70°C / -22°F to 158°F		
CONNECTING CABLE	<ul style="list-style-type: none"> - 10 ft, 4 Conductors - 4P4C or 6P4C Modular Plugs - Straight Connection 		
DIMENSIONS, INCHES (W x D x H)	2.3 x 1.1 x 2.9		
DIMENSIONS, MM (W x D x H)	57 x 28 x 74		
WEIGHT (WITHOUT CABLE), g	32		
WEIGHT (WITHOUT CABLE), lbs	0.07		
FOR USE WITH SPECIFIC INVERTER MODELS	SA-1000K	SK700	ST-1500
	SA-2000K	SK1000	
	SA-3000K	SK1500	
		SK2000	
		SK3000	