

# mWAVE-A1

## MAP-200 Compact Multi-Wavelength Wavemeter



### Key Benefits

- Industry's most compact multi-wavelength meter
- Covers extended C-band (191.1 – 196.4 THz) for telecom manufacturing
- $\pm 3$  pm absolute accuracy
- Seamlessly transitions from R&D to manufacturing environments
- Works alongside other MAP modules in the MAP-230B and MAP-280
- No moving parts

### Key Features

- Extended C-band acquisition range
- Multi-wavelength meter
- Easy-to-use tabulated results

### Applications

- DWDM transmission systems
- Optical sources
- Transponders and line cards

The innovative JDSU Wavemeter module is the most compact solution available. It is a richly featured multi-wavelength meter that works in MAP-230B and MAP-280 mainframes and can be controlled through an easy-to-use GUI or the MAP-200 automation interface.

Based on coherent detection techniques, it provides unprecedented frequency resolution to precisely report the power level and central frequencies of densely spaced optical signals as close as 2 GHz.

This ground-breaking solution is ideal for both lab and manufacturing test systems where reliability, compactness, and performance are critical.

### Platform Compatibility

MAP-230B



3-slot mainframe

MAP-280/MAP-280R



8-slot mainframe

**Specifications (at 25°C over the entire frequency range)**
**Spectral**

Optical frequency (wavelength) range	196.4 – 191.1 THz (1526.44 – 1568.77 nm)
Absolute uncertainty of frequency (wavelength) <sup>1</sup>	±370 MHz (±3 pm)
Minimum signal separation	2 GHz (16 pm)

**Power**

Input power range <sup>2</sup>	–60 to +10 dBm
Max. total input power <sup>3</sup>	+17 dBm
Absolute uncertainty of power level <sup>1,4</sup>	±1 dB
Display resolution	0.01 dB

1. Average of 10 consecutive sweeps.
2. Power of unmodulated single-frequency laser or peak power of modulated signal in 300 MHz optical bandwidth.
3. Total power of all input signals.
4. For input power from –10 to –40 dBm.
5. Over 50 GHz sweep range, no averaging.

**Other**

Return loss	>50 dB
Measurement time <sup>5</sup>	min 1.0 s
Fiber type	9/125 μm single-mode fiber
Connector type	FC/APC
Operating temperature	10 to 40°C
Storage temperature	–20 to +50°C
Humidity	Maximum 95% RH from +10 to +40°C noncondensing
Dimensions	4.06 x 13.26 x 37.03 cm
Weight	1.4 kg
Calibration period	1 year

**Ordering Information**

Description	Part Number
MAP-200 extended C-band wavemeter module	mWAVE-A1CB10
Basic spectrum view for wavemeter	MSUP-WMSPTRM

**Network and Service Enablement Regional Sales**

<b>NORTH AMERICA</b> TOLL FREE: 1 855 ASK-JDSU 1 855 275-5378	<b>LATIN AMERICA</b> TEL: +1 954 688 5660 FAX: +1 954 345 4668	<b>ASIA PACIFIC</b> TEL: +852 2892 0990 FAX: +852 2892 0770	<b>EMEA</b> TEL: +49 7121 86 2222 FAX: +49 7121 86 1222	<a href="http://www.jdsu.com/nse">www.jdsu.com/nse</a>
---	--	---	---	--