

MD PRO


Normally closed proportional solenoid valve

FEATURES

- 2-way normally closed
- Offers automated calibration
- Provides repeatability across its operating range
- Offers a superior combination of value and performance
- Rated for 10 million life cycles

MEDIA COMPATIBILITY

Air, argon, helium, hydrogen, methane, nitrogen, oxygen & others



ELECTRICAL

Power	max. 2 W
Voltage	max. 5.5, 8, 11.5, 13.5, 20 or 29 V _{DC}

PHYSICAL PROPERTIES

Operating environment	0 to 60 °C
Storage temperature	-40 to 70 °C
Length	45.3 mm (1.785 in)
Width	16.5 mm (0.625 in)
Height	17 mm (0.67 in)
Porting	1/8" barbs; manifold mount with 43 µm screen
Weight	63 g (2.2 oz)
Internal volume	0.508 cm ³ (0.031 in ³)
Filtration (recommended)	43 µm
Lubrication	None required
Oxygen clean	Available on special request


MD PRO

Normally closed proportional solenoid valve

PERFORMANCE CHARACTERISTICS

Part no.	Pressure	Vacuum	Orifice sizes	Leak rate ¹	Response
MDPRO4...	0...75 psid	0...27 "Hg (0...13 psi)	0.040" (1.02 mm)	≤0.22 sccm of air (bubble tight)	<30 msec cycling
MDPRO5...	0...100 psid		0.050" (1.27 mm)		
MDPRO6...	0...50 psid		0.065" (1.65 mm)		

FLOW CURVE²



Notes:



¹ sccm denotes Standard Cubic Centimeters per Minute. It is a unit for the flow rate at standard conditions of temperature and pressure. 1000 sccm = 1 slpm.

² slpm denotes Standard Liters per Minute. It is a unit for the flow rate at standard conditions of temperature and pressure. 1 slpm = 1000 sccm.


MD PRO

Normally closed proportional solenoid valve

ELECTRICAL INTERFACE OPTIONS



PNEUMATIC INTERFACE OPTIONS



ORDERING INFORMATION

Series		Model no.		Elastomer		Coil selection			Electrical interface		Pneumatic interface		Cleaning	
		Max. pressure	Orifice size			Max. voltage*	Resistance**	Current***						
Options	MDPRO	4:	75 psid	0.040" (1.016 mm)	V: FKM	A:	5.5 V _{DC}	11 Ω	0.304 A	F: wire leads, 18"	1: manifold mount with screens*	S: standard cleaning		
		5:	100 psid	0.050" (1.270 mm)		B:	8 V _{DC}	23 Ω	0.212 A					
		6:	50 psid	0.065" (1.651 mm)		C:	11.5 V _{DC}	47 Ω	0.152 A					
						D:	13.5 V _{DC}	68 Ω	0.125 A					
						E:	20 V _{DC}	136 Ω	0.091 A					
						F:	29 V _{DC}	274 Ω	0.066 A					
						* max. voltage for continuous full flow, ambient temp. 55 °C ** coil resistance for room temp. *** input current for full flow					* 43 μm screen (port 2)		* this option will affect price; contact Sensortech for details	
Example: MDPRO		4	V		A	F			8	S				

Note: Not all combinations might be available. Please contact First Sensor for further information.

First Sensor reserves the right to make changes to any products herein. First Sensor does not assume any liability arising out of the application or use of any product or circuit described herein, neither does it convey any license under its patent rights nor the rights of others.