

KTE6000 / KTU6000 Series

OEM pressure transmitters for industrial media



FEATURES

- 250 mbar to 400 bar, 5 to 6000 psi gage¹ or absolute¹¹ pressure
- For many industrial gases and liquids
- 0...10 V, 0.5...4.5 V, 0...5 V, 1...6 V or 4...20 mA output
- Field interchangeable
- EMC according to EN 61326-1⁸

MEDIA COMPATIBILITY

Wetted materials:

Stainless steel 1.4404 (316L), ceramic Al_2O_3 , NBR (FKM)

Housing:

Stainless steel, protection class IP 65 (according to DIN EN 60529, NEMA 4X)¹



SPECIFICATIONS^{9,10}

Maximum ratings

Supply voltage (reverse polarity protection)

KT...0...	13...32 V
KT...1...	9...32 V
KT...6..., ...7...	8...32 V
KT...4... ²	7...32 V

Maximum load current (source)

KT...0..., ...1..., ...6..., ...7...	1 mA
--------------------------------------	------

Proof pressure³

400 bar/6000 psi devices	1.5 x rated pressure
all others	2 x rated pressure

Environmental

Temperature limits

Storage	-40...85 °C
Operating (media)	-25...85 °C
Electronic (ambient)	-25...85 °C
Compensated	0...70 °C

Vibration (5 to 500 Hz)


10 g_{RMS}

Mechanical shock


50 g

ELECTRICAL CONNECTION

Voltage output device



Current output device



KTE6000 / KTU6000 Series

OEM pressure transmitters for industrial media

COMMON PERFORMANCE CHARACTERISTICS

($V_S=15\text{ V} \pm 0.1\text{ V}$, $T_A=25\text{ °C}$, RH=50 %)

Characteristics			Min.	Typ.	Max.	Unit
Thermal effects (0...70 °C) ⁴	Offset	devices up to 1 bar/15 psi		±0.03	±0.06	%FSO/ °C
		all others		±0.02	±0.04	
	Span			±0.02	±0.04	
Thermal effects (-25...0 °C, 70...85 °C) ⁴	Offset			±0.03		%FSO/ °C
	Span			±0.03		
Non-linearity (BSL), hysteresis and repeatability ⁵	KT...6N...			±0.2	±0.5	%FSO
	all others			±0.1	±0.3	
Long term stability ⁶				±0.1	±0.3	
Output noise (0< f <1 kHz)				±0.1		
Response time (10 to 90 %)	devices up to 350 mbar/5 psi			35		ms
	all others			5		
D/A resolution					11	bit
Power supply rejection	Offset			±0.01		%FSO/V
	Span			±0.02		

INDIVIDUAL PERFORMANCE CHARACTERISTICS

($V_S=15\text{ V} \pm 0.1\text{ V}$, $T_A=25\text{ °C}$, RH=50 %)

0...10 V output ($R_L > 100\text{ k}\Omega$)

Characteristics		Min.	Typ.	Max.	Unit
Zero pressure offset	KT...6N...		5		V
	all others		0	0.1	
Full scale span ⁷		9.9	10	10.1	
Output impedance				25	Ω
Current consumption (no load)			4		mA

0.5...4.5 V output ($R_L > 100\text{ k}\Omega$)

Characteristics		Min.	Typ.	Max.	Unit
Zero pressure offset	KT...6N...		2.5		V
	all others	0.45	0.5	0.55	
Full scale span ⁷		3.95	4	4.05	
Output impedance				25	Ω
Current consumption (no load)			4		mA

KTE6000 / KTU6000 Series

OEM pressure transmitters for industrial media

INDIVIDUAL PERFORMANCE CHARACTERISTICS (cont.)

($T_A = 25\text{ °C}$, $RH = 50\%$, $V_S = 15\text{ V} \pm 0.1\text{ V}$)

0...5 V output ($R_L > 100\text{ k}\Omega$)

Characteristics		Min.	Typ.	Max.	Unit
Zero pressure offset	KT...6N...		2.50		V
	all others		0	0.05	
Full scale span ⁷		4.95	5.00	5.05	
Output impedance				25	W
Current consumption (no load)			4		mA

1...6 V output ($R_L > 100\text{ k}\Omega$)


Characteristics		Min.	Typ.	Max.	Unit
Zero pressure offset	KT...6N...		3.50		V
	all others	0.95	1.00	1.05	
Full scale span ⁷		4.95	5.00	5.05	
Output impedance				25	Ω
Current consumption (no load)			4		mA

4...20 mA output ($R_L = 100\text{ }\Omega$)

Characteristics		Min.	Typ.	Max.	Unit
Zero pressure offset	KT...6N...		12.0		mA
	all others	3.9	4.0	4.1	
Full scale span ⁷		15.9	16.0	16.1	
Power consumption ($I_L = 20\text{ mA}$)			250		mW

LOAD LIMITATION

4...20 mA output version




KTE6000 / KTU6000 Series


OEM pressure transmitters for industrial media

OUTLINE DRAWING


KT...T...




KT...Q...



KT...L...



KT...O... (flush mount)



mass: approx. 200 g

dimensions in mm (inches)


Pin	Output	
	Voltage	Current
1	+Vs	+Vs
2	-Vs	-Vs
3	Vout	N/C
⊕	Case	Case

KTE6000 / KTU6000 Series

OEM pressure transmitters for industrial media

RECOMMENDED ACCESSORY


Plug **DIN EN 175301-803 A** and profile washer included in delivery.



Note:

For proper function of all gage devices the gage port must be vented to the atmosphere through the connector/cable assembly.

For a complete **connector/cable assembly** use order no. **ZK000110-x** (x=cable lengths in m, max. 10 m).



PIN CONNECTION	
Pin	Flying lead end
1	Brown
2	Yellow
3	Green
⊕	White and bare

dimensions in mm


Specification notes:

1. IP 65 protection is given when the connector is locked with a rubber washer. For proper function the gage port is vented to the atmosphere through the connector/cable assembly. Thus the cable end must have access to the ambient pressure.
2. The minimum supply voltage is directly proportional to the load resistance seen by the transmitter (see load limitation diagram).
3. Proof pressure is the maximum pressure which may be applied without causing damage to the sensing element.
4. Thermal effects are relative to 25 °C. Signal is clamped at 0 V.
5. Non-linearity refers to **Best Straight Line** fit. Hysteresis is the maximum output difference at any point within the operating pressure range for increasing and decreasing pressure.
6. Long term stability is the change in output after one year.
7. Full scale span is the algebraic difference between the output signal for the highest and lowest specified pressure.
8. Surge immunity according to EN 61000-4-5 on request for current output devices.
9. CE-labelling is in accordance with 2004/108/EC.
10. The pressure transmitters must not be used as safety accessories according to article 1, 2.1.3 of the directive 97/23/EC.
11. Available for pressure ranges from 1 bar (15 psi) absolute upwards only.

KTE6000 / KTU6000 Series

OEM pressure transmitters for industrial media

ORDERING INFORMATION



Other pressure ranges and options are widely available. Please contact First Sensor.

First Sensor reserves the right to make changes to any products herein. First Sensor does not assume any liability arising out of the application or use of any product or circuit described herein, neither does it convey any license under its patent rights nor the rights of others.