The CVA-118 is a high-performance, compact 18-inch active subwoofer with 700 watts of efficient power output. The legendary Cerwin-Vega woofer design is reflected in this 18-inch woofer offering maximum bass performance with extreme power handling and exceptional low-frequency response. The CVA-118 features built-in amplification for an integrated, all-in-one solution with a powerful 1400 watts of peak power output. A unique and striking cast aluminum grille protects the woofer from, while doubling as a heat-sink to minimize power compression and optimizing driver performance. Housed in a compact hardwood enclosure design the size of a standard 15-inch subwoofer footprint, the CVA-118 is highly portable and durable with the option of a durable Coolex® polyurethane paint or high-grade black carpet finish. Along with XLR and 1/4" TRS connectors, the CVA-118 has Master/ Slave output connectors that allow for multiple CVA subwoofers to be daisy-chained together using a single signal. This compact active sub also features a 35 mm pole-mount socket to accommodate a satellite speaker for full range performance.



The Details

Benefit Feature Advantage best-in-class, top-grade Legendary Cerwin-Vega quality low frequency Bass Performance system design and full body bass response Custom 18-inch Cerwinhighly qualified, extreme power handling customized woofer design Vega Woofer and exceptional cone excursion Built-in System amplifier designed to truly portable and flexible Amplification optimize 18-inch woofer all-in-one system performance Master/ Slave Output allows for daisy-chaining reduces cable multiple subs connections, and system expansion Cast Aluminum Grille durable grille design that reduces power protects the woofer and compression so you can acts as a heat sink play louder and longer Hardwood Enclosure rugged enclosure reliable cabinet that will with Paint or Carpet construction material with last through harsh Finish optional finish conditions Top-mount 35 mm Pole accommodates a satellite allows for flexible full Socket speaker for full range range system performance configurations

Specifications

Power:	continuous 700 watts peak 1400 watts
Frequency Response:	41 Hz - 135 Hz (±3 dB)
Frequency Range:	38 Hz - 135 Hz (-10 dB)
Max SPL:	131 dB
Crossover:	LPF 65 Hz - 130 Hz HPF 35 Hz
Connectors:	inputs XLR/ F Balanced (x2) 1/4" TRS (x2
	outputs XLR/ M (x2) XLR/ M Slave
Controls:	HPF 65 Hz, 85 Hz, 130 Hz variable LPF 65 Hz, 130 Hz polarity 0 - 180 degrees
Driver:	model, SW18C, size 18"
Voice Coil:	3"
Enclosure / Finish	Hardwood Coolex® Paint or Black Carpet
Dimensions:	25.0" x 21.0" x 23.5" 635 mm x 533 mm x 597 mm
Weight:	subwoofer 115 lb (52.2 kg shipping 121 lb (54.8 kg)

