



SDS-525T

STRUCTURAL DESIGN SERIES™



OVERVIEW

The new Cerwin-Vega! Professional SDS-525T is a voice matched, full range system specifically designed for professional applications, including foreground and background music playback. Available in black or white, the SDS-525T includes a proprietary, adjustable-mounting bracket.

Every SDS-525T features:

- Versatile mounting brackets for a variety of placement options
- Small, high-impact, polyresin cabinets with sleek contours and durable metal grilles
- Push terminal connections
- Video Shielding
- Weather-resistant cabinets
- Master cartons containing three pairs of speakers

INSTALLATION

The adjustable bracket will accommodate both wall and ceiling installations. The bracket with the circular adapter is intended for ceiling mounting to a threaded rod and offers a maximum tilt angle of 60°. Without the circular adapter the bracket can be screwed directly to the wall with a maximum tilt angle of 45°.



SPECIFICATIONS

FREQUENCY RESPONSE

68 Hz to 20 kHz (-10dB)

DESIGN

2-way, bass-reflex

Internal Transformer for use in 100V / 70.7V
Constant Voltage Distribution Systems

CROSSOVER FREQUENCY

3.5 kHz

POWER HANDLING

150 watts, IEC-268-5

IMPEDANCE

4 ohms, nominal

SENSITIVITY

88 dB @ 1 watt/meter

VIDEO SHIELDED

Yes

DRIVERS

(1) 1" mylar-dome tweeter

(1) 5.25" co-polymer woofer with butyl-rubber surround

DIMENSIONS (H x W x D)

8-3/8" x 6-7/16" x 4-1/8"
(unpacked, each)

WEIGHT

5.6 lb.



USA: Cerwin-Vega!, Inc. • 9340 De Soto Ave., • Chatsworth, CA • 91311
Phone: 1-818-534-1500 • Fax: 1-818-534-1590 • Email: info@cerwin-vega.com

Cerwin-Vega! is a division of The Stanton Group

Cerwin-Vega! reserves the right to make changes to product specifications and design at any time

LITP00006