

C2N-FT-TPS4-U

FlipTop™ Touch Screen Control Center, no AC Outlet

- > Stylish flush-mount FlipTop™ housing
- > Integrated 3.6" active matrix color touch screen
- > 10 translucent white backlit pushbuttons
- > Customizable audio feedback
- > Easy pull-out universal cable management
- > Optional cable retractors
- > Ethernet and Cresnet® communications
- > Black anodized finish

The C2N-FT-TPS4-U FlipTop™ Touch Screen Control Center by Crestron® provides an ingenious control and connectivity solution in a stylish flush mount tabletop design. Popping open the “FlipTop” lid exposes a color touch screen, perfectly angled for easy access and intuitive operation. The built-in cable storage compartment keeps interface cables at the ready for plugging in laptop computers, mobile devices, AV sources, and other equipment.

FlipTop Touch Screen Control Centers are ideal for use with AV distribution systems like Crestron [DigitalMedia™](#), allowing the signal transmitters and receivers to be installed out of sight beneath the tabletop, with the user interface cables organized neatly within the cable storage compartment. The integrated touch screen can be used to select sources, adjust the volume, and control display devices among other functions.

FlipTop Housing

Handsomely finished in black anodized, the C2N-FT-TPS4-U lends a contemporary metallic accent to conference tables and podiums. It mounts flush in virtually any flat, horizontal surface up to 1-15/16 inch (49 mm) thick for a clean, low-profile appearance.

Integrated Touch Screen

The 3.6" color touch screen provides a fully-customizable user interface for control of AV, lighting, and other functions. Ten backlit pushbuttons are included for quick access to commonly used functions. Custom engraving of the faceplate is available to designate each button.^[1] To prevent accidental button presses, the touch screen and pushbuttons are automatically disabled whenever the lid is not fully opened.

Audio Feedback

Customized audio files can be loaded to add another dimension to the touch screen graphics and pushbuttons using personalized sounds, button feedback, and voice prompts.

Cable Storage Compartment

The C2N-FT-TPS4-U provides easy pull-out storage for [Crestron Certified Interface Cables](#)^[2] and a wide variety of other AV, data, and communication cables. Eight grommeted holes are provided in the bottom of the storage compartment to accommodate either premade or custom cables, allowing each cable to be pulled out smoothly as needed. When not in use, the user end of each cable stows neatly within the storage compartment while excess cable simply drops out-of-sight below the box.



Cable Retractor Option

For an even more refined cable management solution, the C2N-FT-TPS4-U accommodates up to four Crestron [CBLR Series Cable Retractors](#). Crestron cable retractors feature a patent-pending, lever-actuated retraction mechanism that ensures smooth operation while eliminating hanging cable loops beneath the table.^[3]

SPECIFICATIONS

Touch Screen Display

Display Type: TFT active matrix color LCD
Size: 3.6 inch (91 mm) diagonal
Aspect Ratio: 4:3 QVGA
Resolution: 320 x 240 pixels
Brightness: 300 nits (cd/m²)
Contrast: 300:1
Color Depth: 16-bit, 64k colors
Illumination: Edgelit LED
Viewing Angle: ±80° horizontal, +80°/-50° vertical
Touch Screen: Resistive Membrane

Buttons

Hardkeys: (10) Translucent white backlit pushbuttons, programmable
Reset: (1) Miniature pushbutton for touch screen hardware reset, accessible through small hole above touch screen display

C2N-FT-TPS4-U FlipTop™ Touch Screen Control Center, no AC Outlet

Memory

DRAM: 16 MB
Flash: 8 MB
Maximum Project Size: 7 MB

Graphic Engine

16-bit non-palette graphics; 65,536 colors; Synapse™ image rendering algorithm; PNG translucency, multi-mode objects, dynamic graphics, full-motion (60 fps) animation

Communications

Ethernet: 10/100 Mbps, auto-switching, auto-negotiating, auto-discovery, full/half duplex, DHCP
Cresnet®: Cresnet slave mode

Audio

Audio Feedback: WAV format, 8 bit PCM, mono, 8 kHz sampling rates
Amplification: 1 Watt for built-in speaker

Connectors - Bottom Panel

LAN: (1) 8-wire RJ45 with 2 LED indicators;
10Base-T/100Base-TX Ethernet port;
Green LED indicates Ethernet link status;
Yellow LED indicates Ethernet activity
NET: (2) 4-pin 3.5mm detachable terminal blocks;
Cresnet slave ports, paralleled;
Connect to Cresnet control network or power supply
G: (1) 6-32 screw, chassis ground lug

Power Requirements

Cresnet Power Usage: 5 Watts (0.21 Amp @ 24 Volts DC)

Environmental

Temperature: 41° to 104°F (5° to 40°C)
Humidity: 10% to 90% RH (non-condensing)

Enclosure

Chassis: Metal, black
Cover: Aluminum, black anodized finish
Faceplate: Plastic, black, engravable⁽¹⁾
Mounting: Flush tabletop mount, 1-15/16 in (49 mm) maximum surface thickness, 6-1/8 in (155 mm) deep x 7-1/4 in (184 mm) wide cutout (template provided)

Dimensions

Height: 5.76 in (147 mm) with lid closed
Width: 7.67 in (195 mm)
Depth: 6.55 in (167 mm), 8.09 in (206 mm) with mounting brackets

Weight

4.05 lb (1.84 kg)

MODELS & ACCESSORIES

Available Models

C2N-FT-TPS4-U-B: FlipTop™ Touch Screen Control Center, no AC Outlet, Black Anodized

Available Accessories

FT-TPS4-FP-B: Engravable Faceplate for FlipTop™ Boxes with 3.6" Touch Screens
PW-2407RU: 18 Watt Cresnet® Power Supply, US/International
CBLR Series: Cable Retractors for FlipTop™ Boxes
CBLRA-BRKT-4-FT: Cable Retractor Mounting Bracket for Large FlipTop™ Boxes
CBLRA-BRKT-4-H: Horizontal Mounting Option for CBLRA-BRKT-4-FT
CBLRA-INSERT-BLANK: Blank Insert for Cable Retractor Mounting Brackets
CBLRA-INSERT-2WIRE: 2-Wire Insert for Cable Retractor Mounting Brackets
CBL Series: Crestron® Certified Interface Cables
CRESNET-NP: Cresnet® Control Cable, non-plenum
CRESNET-P: Cresnet® Control Cable, plenum
CRESNET-HP-NP: Cresnet® "High-Power" Control Cable, non-plenum

Notes:

1. Custom engraving sold separately.
2. Interface cables sold separately.
3. Adding the cable retractor option removes all eight of the standard grommets cable holes. Cable retractors and related accessories sold separately. See the [CBLR](#) spec sheet for more information.

This product may be purchased from an authorized Crestron dealer. To find a dealer, please contact the Crestron sales representative for your area. A list of sales representatives is available online at www.crestron.com/salesreps or by calling 800-237-2041.

Specifications subject to change without notice. Crestron is not responsible for errors in typography or photography.

The specific patents that cover Crestron products are listed online at: patents.crestron.com.

Cresnet, Crestron, DigitalMedia, FlipTop, Synapse, and the Crestron logo are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. ©2012 Crestron Electronics, Inc.

C2N-FT-TPS4-U FlipTop™ Touch Screen Control Center, no AC Outlet

