

C2N-TAMFMXM

AM/FM and XM[®] Satellite Radio Tuner

- > Provides discrete AM/FM and XM[®] tuners in one box^[1]
- > Enables interactive control using touch screens and mobile devices^[2]
- > Support for metadata enables display of station names, song titles, artists, and other details^[3]
- > Onboard user preset capability
- > Includes independent analog and digital audio outputs^[4]
- > Native Crestron[®] system integration via Cresnet[®]
- > Easy setup from front panel or software



The C2N-TAMFMXM provides one AM/FM tuner and one XM[®] Satellite Radio tuner^[1] for use with a Crestron[®] multiroom audio system. Discrete audio outputs are provided for each tuner allowing both tuners to be operated independently and simultaneously. The AM/FM tuner features a stereo analog output, while the XM tuner features both analog and SPDIF digital outputs. Control of each tuner is available through the LCD front panel, as well as from Crestron touch screens, computers and mobile devices via a Crestron control system.

The C2N-TAMFMXM is an ideal companion to the [C2N-AMP-4X100](#) 4 Room Audio System or Sonnex[™] Multiroom Audio System ([SWAMP-24X8](#)). Multiple tuners can be installed to accommodate any number of listening zones, allowing listeners in each room to enjoy their choice of music, news, talk, or sports.

SPECIFICATIONS

AM Tuner

Frequency Range: 530 to 1710 kHz (9 or 10 kHz steps)
Sensitivity: 3.5 μ V (RF input level 10dB S+N/N)
Selectivity: 10kHz
Alternate Channel Selectivity: 55dB
Image Rejection: 35dB
IF Rejection: 60dB

FM Tuner

Frequency Range: 87.50 to 108 MHz (50 or 100 kHz steps)
Usable Sensitivity: 11dBf mono; 60dBf stereo
S/N Ratio: 64dB @ 65dBf mono; 56dB @ 65dBf stereo
IF Rejection: 100dB
AM Rejection: 55dB
Stereo Separation: 27dB

XM[®] Tuner (analog)

THD+N: <0.01% @1kHz
S/N Ratio: >97dB balanced, >95dB unbalanced, 20Hz-22kHz A-weighted
Crosstalk: >-90dB 20Hz-22kHz

Connectors

AM-FM AUDIO OUT L,R: (2) RCA female;
AM/FM tuner unbalanced stereo line-level audio output

XM AUDIO OUT L,R: (2) RCA female;
XM tuner unbalanced stereo line-level audio output

XM AUDIO OUT SPDIF: (1) RCA female;
XM tuner S/PDIF coaxial digital audio output

FM ANTENNA: (1) IEC 169-2 coaxial (IEC-to-F adapter included);
FM wire antenna included;
Impedance: 75 Ohms

AM ANTENNA: (1) 2-pin spring-loaded terminal;
AM shielded loop antenna included;
Impedance: 50 Ohms

XM ANTENNA: (1) F-type coaxial (F-to-SMB adapter included);
Indoor/outdoor high-gain antenna w/20 ft cable included;
Available Power: 200 mA @ 5 Volts DC

NET: (2) 4-pin 3.5mm detachable terminal blocks;
Cresnet[®] slave ports, paralleled;
Connect to Cresnet control network

24 VDC 2A: (1) 2.1mm barrel DC power jack;
24 Volt DC power input (PW-2407W power pack included)

G: (1) 6-32 screw, chassis ground lug

C2N-TAMFMXM AM/FM and XM[®] Satellite Radio Tuner

Display

Green LCD alphanumeric, 2 lines x 20 characters per line;
Displays setup and control menus, and channel and content information

Controls & Indicators

AM, FM, XM: (3) pushbuttons, select which tuner band to control
DISP: (1) pushbutton, press to display channel and content information
MENU: (1) pushbutton, press to display a list of menu options
▲, ▼: (2) pushbuttons, used to navigate the menu and select channels
ENTER: (1) pushbutton, press to execute a menu item
NET: (1) amber LED, indicates communication with the Cresnet system
RESET: (1) recessed miniature pushbutton for hardware reset

Power Requirements

Power Pack: 0.75 Amps @ 24 Volts DC;
100-240 Volts AC, 50/60 Hz power pack, model PW-2407W included

Cresnet Power Usage: none

XM Antenna Power: 200 mA @ 5 Volts DC

Environmental

Temperature: 32° to 113°F (0° to 45°C)
Humidity: 10% to 90% RH (non-condensing)
Heat Dissipation: 27 BTU/Hr

Enclosure

Chassis: Aluminum w/polycarbonate label overlay
Front Panel: Plastic, black with polycarbonate label overlay

Dimensions

Height: 2.36 in (60 mm) with feet
Width: 8.12 in (206 mm)
Depth: 5.93 in (151 mm)

Weight

4.30 lb (1.95 kg)

MODELS & ACCESSORIES

Available Models

C2N-TAMFMXM: AM/FM and XM[®] Satellite Radio Tuner

Included Accessories

PW-2407W: Wall Mount Power Pack 24VDC, 0.75A (Qty. 1 included)

Available Accessories

C2N-TXM-C50: Antenna Extension Cable for XM[®] Radio, 50 ft

SRD Series: Satellite Radio Antenna Distribution Products

CBL-RCA: Crestron[®] Certified RCA S/PDIF Audio Interface Cables

CBL-RCA2: Crestron[®] Certified RCA Stereo Audio Interface Cables

Notes:

1. XM Satellite Radio requires subscription. Contact Sirius XM Radio Inc. for details.
2. Crestron control system and programming required.
3. FM radio metadata display dependent upon individual station support for RDS/RBDS.
4. Digital output is for XM tuner only.

This product may be purchased from an authorized Crestron dealer. To find a dealer, please contact the Crestron sales representative for your area. A list of sales representatives is available online at www.crestron.com/salesreps or by calling 800-237-2041.

Specifications subject to change without notice. Crestron is not responsible for errors in typography or photography.

The specific patents that cover Crestron products are listed online at: patents.crestron.com.

Cresnet, Crestron, Sonnex, and the Crestron logo are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. XM and the XM logo are either trademarks or registered trademarks of Sirius XM Radio Inc. in the United States and/or other countries. Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. ©2012 Crestron Electronics, Inc.

C2N-TAMFMXM AM/FM and XM[®] Satellite Radio Tuner

