

CLS-EXP-DIM

iLux® Dimmer Expansion Module

- > Works with Crestron iLux®, CLW^[2], DIN, and CLX series dimmers
- > Emulates the characteristics of the dimmer that is controlling it
- > Up to 5 Expansion Modules can be connected to a single iLux dimmer channel
- > Supports 120, 230, and 277 Volt LED^[1], incandescent, NCC, MLV, and 2-wire dimmable fluorescent loads
- > Includes threshold adjustment for setting minimum fluorescent dimming level
- > Built-in air gap relay at the output
- > Mounts to a wall or above a suspended ceiling
- > CEC Title 24 2013 Compliant

The CLS-EXP-DIM enables the expansion of Crestron iLux® Integrated Lighting System (CLS-C6 series) and other Crestron® lighting dimmers to support 120, 230, or 277 Volt loads up to 16 Amps. It allows any output channel of the iLux system to dim a fully loaded circuit of LED^[1], incandescent, magnetic low-voltage, neon/cold cathode, or 2-wire dimmable fluorescent lighting loads. It is also compatible with CLW-Series^[2] in-wall dimmers and select CLX-Series lighting control modules^[3].

The CLS-EXP-DIM is designed for mounting to a vertical surface^[4], and can be installed in an environmental air-handling space above a suspended ceiling. Conduit knockouts are provided on the bottom and lower sides. All connections are made via screw terminals behind the front cover.

SPECIFICATIONS

Load Ratings

Dimmer Channels: 1

Load Rating: 16 Amps

Minimum Load: 15 Watts at 120 Volts, 25 Watts at 230 Volts, 30 Watts at 277 Volts

Load Types: LED^[1], incandescent, neon/cold cathode, magnetic low voltage, 2-wire dimmable fluorescent (Advance Mark 10 Powerline® or equivalent)

Input Voltages

Line Power: 120 to 277 Volts AC, 50/60 Hz

Control Input: 120 or 230 Volts AC, 50/60 Hz, phase independent of line power and load

Connections

INPUT, CTRL: (1) Captive screw terminal^[5], control input from CLS(l)-C6 Series, CLW-DIM Series^[2], CLX(l)-DIM Series, GLX-DIM6, GLXX-2DIM8, DIN-1DIM4, or DIN-1DIMU4 dimmers;

Note: Presents a 25 Watt load to the controlling dimmer; a maximum of 5 CLS-EXP-DIM modules may be connected to the controlling dimmer, which cannot be wired to control any other loads besides the CLS-EXP-DIM modules



INPUT, NEUT: (1) Captive screw terminal^[5], neutral connection for control input

OUTPUT, DIM OUT: (1) Captive screw terminal^[5], dimmed load output

OUTPUT, (NC): (1) Captive screw terminal^[5], not used (do not connect)

OUTPUT, HOT: (1) Captive screw terminal^[5], line power input

OUTPUT, NEUT: (1) Captive screw terminal^[5], neutral connection for line power input and load

GROUND: (1) 3-terminal chassis ground bus bar

Controls & Indicators

FLUORESCENT OFF THRESHOLD: (1) recessed screwdriver-adjustable trim pot behind removable cap, adjusts minimum brightness level

STATUS: (1) Red LED behind front panel, illuminates when load output is on

POWER: (1) Green LED behind front panel, indicates line power is applied to the HOT terminal

Environmental

Temperature: 32° to 104°F (0° to 40°C)

Humidity: 10% to 90% RH (non-condensing)

Heat Dissipation: 140 BTU/Hr at maximum load, 16A

Enclosure

Surface mount^[4] module with (2) integral mounting flanges, galvanized steel w/gray matte powder coat front panel, extruded aluminum heat sink, (4) 1/2" or 3/4" conduit knockouts provided on bottom and lower left & right sides

Dimensions

Height: 8.82 in (224 mm)

Width: 6.39 in (163 mm)

Depth: 3.18 in (81 mm)

CLS-EXP-DIM iLux® Dimmer Expansion Module

Weight

3.34 lb (1.52 kg)

Standards & Certifications

UL Listed
CEC Title 24 2013 Compliant

MODELS

Available Models

CLS-EXP-DIM: iLux® Dimmer Expansion Module

Notes:

1. For a list of compatible ballasts, visit www.crestron.com/lightingcompatibility (PDF)
2. CLW-Series device must have a dedicated neutral.
3. Compatible only with forward-phase dimming modules.
4. Must be oriented upright, mounted to a vertical surface, with 6 inches (153 mm) minimum spacing above and below for proper ventilation and heat dissipation.
5. Captive screw terminals accept up to two 22 to 12 AWG (0.34 to 4.0 mm²) wires per terminal.

This product may be purchased from an authorized Crestron dealer. To find a dealer, please contact the Crestron sales representative for your area. A list of sales representatives is available online at www.crestron.com/salesreps or by calling 800-237-2041.

The specific patents that cover Crestron products are listed online at: patents.crestron.com.

Crestron, the Crestron logo, and iLux are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Mark 10 Powerline is either a trademark or registered trademark of Koninklijke Philips Electronics N.V in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography. Specifications are subject to change without notice.
©2014 Crestron Electronics, Inc.

CLS-EXP-DIM iLux® Dimmer Expansion Module

CAD DRAWINGS

