

## In-Wall Switch, 230VAC

- > Field replaceable and engravable buttons
- > Available in anthracite or white finishes
- > infiNET EX® robust communication
- > Configurable up to 6 buttons
- > Screw-clamp connectors for easy installation
- > Stylish bargraph LED array provides real-time status feedback

The CLWI-SWEX delivers native Crestron® control to any light or other switched load, in new or retrofit 230 Volt applications. Featuring reliable infiNET EX® wireless technology, the CLWI-SWEX can be installed in virtually any location thanks to reliable mesh networking. Support for up to 2 Amp loads makes this switch perfect for most applications.

### Field-Replaceable and Engravable Buttons

The CLWI-SWEX features engravable buttons that can be swapped out in the field. Change of room décor or functionality is easy to handle long after the dimmer or switch has been installed. Positive snap-on fittings require no tools. Configure the dimmer or switch with a large rocker, or any combination of up to two adjacent half-size rockers or triple button pad. Each CLWI-SWEX ships with a full assortment of blank buttons as well.


### Integrated Keypad

Because the CLWI-SWEX is attached to the Crestron network, it can also function as a keypad, sending commands to trigger whole-room lighting scenes or distributed audio functions. Supporting up to six buttons, the in-wall dimmer or switch serves as a great user control interface in any Crestron system. Its single-box form factor maximizes control capability in a small space while increasing the opportunity for Crestron control in every room. Also available are aesthetically matched standalone keypads which use Cresnet® or infiNET EX communications.

### infiNET EX

Ultra-reliable infiNET EX wireless technology provides steadfast two-way RF communications throughout a residential or commercial structure without the need for physical control wiring. Employing a 2.4 GHz mesh network topology, each infiNET EX device functions as an expander, passing command signals through to every other infiNET EX device within range (approximately 150 feet or 46 meters indoors), ensuring that every command reaches its intended destination without disruption<sup>[1]</sup>.

The CLWI-SWEX communicates with a Crestron control system via an infiNET EX Wireless Gateway (model CEN-RFGW-EX, DIN-AP3MEX, or MC3<sup>[2]</sup>). Up to 100 infiNET EX devices may coexist on a single wireless network, and every non-battery-powered device that is added to the network effectively increases the range and stability of the entire network by providing multiple redundant signal paths<sup>[1]</sup>. Built-in Dynamic Frequency Allocation continuously monitors RF conditions, automatically selecting the clearest channel to prevent interference from neighboring networks, cordless phones, and microwaves.



### Streamlined Installation

In addition to field replaceable buttons, the CLWI-SWEX features screw-clamp connectors for simplified wiring while reducing installation time and material costs. So slim, the CLWI-SWEX can be installed in square gang boxes making them the perfect choice for both new and retrofit projects.

## SPECIFICATIONS

### Load Ratings

**Load Types:** Incandescent, Tungsten-Halogen, Magnetic Low Voltage, CFL, Fluorescent, Electronic Low Voltage, LED

**Maximum Load:** 2 Amps/AX

### Power Requirements

230 Volts AC, 50Hz, line power

### Controls

**Buttons:** Configurable for 1 rocker (up/down), or any combination of up to 2 small rockers and/or 2 three-button pad; maximum layout contains 6 buttons; each press configurable for up to 3 discrete functions via single click, double click and hold; programmable via control system

### LED Indicator

**Feedback:** Up to (10) White LEDs, depending on button configuration

### Wireless

**RF Transceiver:** infiNET EX® 2-way RF, 2.4 GHz ISM Channels 11-26 (2400 to 2483.5 MHz), default channel 15; IEEE 802.15.4 compliant

**Range (typical):** 150 ft (46 m) indoor, 250 ft (76 m) outdoor to nearest mesh network device(s); subject to site-specific conditions and individual device capabilities<sup>[1]</sup>

**Gateway:** Requires an infiNET EX gateway<sup>[2]</sup>

# CLWI-SWEX In-Wall Switch, 230VAC

## Connections

---

**Hot:** (1) 1.5 - 2.5 mm<sup>2</sup> (14-12 AWG), screw terminal, line power input  
**Neutral:** (1) 1.5 - 2.5 mm<sup>2</sup> (14-12 AWG), screw terminal, neutral input  
**Load:** (1) 1.5 - 2.5 mm<sup>2</sup> (14-12 AWG), screw terminal, load output  
**Ground:** (1) screw post, ground

## Environmental

---

**Temperature:** 32° to 104°F (0° to 40°C)  
**Humidity:** 10% to 90% RH (non-condensing)

## Enclosure

---

1-gang mountable in a 35 mm deep square or round electrical box; gangable in horizontal and vertical positioning; Requires faceplate (not included)<sup>[3]</sup>

## Dimensions

---

**Height:** 2.8 in (71 mm)  
**Width:** 2.9 in (74 mm)  
**Depth:** 1.3 in (32 mm) including front face w/ buttons

## Weight

---

3 oz (85 g)

and finishes up to 5-gang in size. Contact Crestron International by phone: +32.15.50.99.50 or email: [info@crestron.eu](mailto:info@crestron.eu).

This product may be purchased from an authorized Crestron dealer. To find a dealer, please contact the Crestron sales representative for your area. A list of sales representatives is available online at [www.crestron.com/salesreps](http://www.crestron.com/salesreps) or by calling 800-237-2041.

The specific patents that cover Crestron products are listed online at: [patents.crestron.com](http://patents.crestron.com).

Crestron, the Crestron logo, 3-Series, 3-Series Control System, Cresnet, Crestron Green Light, and infiNET EX are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography. Specifications are subject to change without notice. ©2014 Crestron Electronics, Inc.

## MODELS & ACCESSORIES

### Available Models

---

**CLWI-SWEX-ANTH:** In-Wall Switch, 230VAC, Anthracite  
**CLWI-SWEX-W:** In-Wall Switch, 230VAC, White

### Available Accessories

---

**CEN-RFGW-EX:** infiNET EX® Wireless Gateway  
**CEN-RFGW-EX-PWE:** infiNET EX® Wireless Gateway w/PoE Injector  
**MC3:** 3-Series Control System® w/infiNET EX®  
**DIN-AP3MEX:** DIN Rail 3-Series® Automation Processor w/infiNET EX®  
**CLW-EXPEX-GD-W-T:** infiNET EX® Wireless Expander, Ground Pin Down, White Textured  
**GLA-EXPEX:** Crestron Green Light® Wireless Expander for infiNET EX® Networks

### Notes:

1. Any infiNET EX device that provides expander functionality will effectively extend the range of the wireless network beyond the initial range of the gateway. Battery-powered infiNET EX devices do not provide expander functionality. Wireless networks composed predominantly of battery-powered devices may need additional infiNET EX expanders, such as the CLW-EXPEX or GLA-EXPEX (sold separately), or other non-battery powered infiNET EX devices to ensure proper functionality of the network and battery life for the devices. Refer to the **Best Practices for Installation and Setup of Crestron RF Products, Doc. #6689** for complete system design guidelines, or contact [Crestron True Blue Support](#) for further assistance.
2. Item(s) sold separately.
3. Faceplate not included. Requires an FP-INTENSE or FP-PURE faceplate, available in 18 colors

# CLWI-SWEX In-Wall Switch, 230VAC

## CAD DRAWINGS

