

## DigitalMedia™ Ultra Cable, Low Smoke Zero Halogen

- > Ultra high-bandwidth CAT7a shield twisted pair (S/FTP) cable
- > Enables lossless distribution of 4K and Ultra HD video signals at distances of 330 ft (100 m) via DM 8G+™ or HDBaseT®
- > Ensures Crestron® guaranteed performance for DigitalMedia 8G+™ systems
- > Exceeds HDMI® specifications requiring less than one pixel error per billion
- > Qualified for use with 10-Gigabit Ethernet data networks
- > Every spool individually tested and certified
- > Measurement markings on the outer jacket
- > Low smoke zero halogen flame rated
- > Meets IEC 60332-1 specifications
- > Sold only in Europe

Crestron® DigitalMedia™ Ultra Cable (DM-CBL-ULTRA-LSZH) is a high-bandwidth CAT7a shielded twisted pair (S/FTP) cable that is engineered to deliver optimum performance for 10 gigabit data networking and 4K ultra high-definition AV signal distribution applications. It is precision manufactured and tested to exceed HDMI® specifications requiring less than one pixel error per billion at distances up to 330 ft (100 m).

DigitalMedia (DM®) Ultra Cable provides a Crestron guaranteed wiring solution for use with Crestron DigitalMedia 8G+™ (DM 8G+™) devices, and is also highly recommended for use with HDBaseT® and other CATx based video and audio systems. DM Ultra Cable is qualified for use with 10-Gigabit Ethernet and anywhere else a high-quality shielded CAT5e, CAT6, or CAT7 cable is required.

DM Ultra Cable is easily terminated using Crestron [DM-CONN](#) shielded RJ45 type connectors. No crimping tool is required, affording fast and reliable termination in the field.<sup>[1]</sup>

DM-CBL-ULTRA-LSZH is a “Low Smoke Zero Halogen” type cable that meets the requirements for use in Europe per IEC 60332-1 specifications. It is available only through Crestron International in Belgium.

### SPECIFICATIONS

#### Construction

S/FTP with four individually shielded twisted pairs, overall shield, and overall jacket

#### Electrical & Performance

**Mutual Capacitance:** ≤5.6 nF / 100 m @ 1 kHz

**Velocity of Propagation:** 74% nominal

**Delay Skew:** ≤25 ns / 100 m

**Conductor DC Resistance:** ≤85 Ohms / km @ 20°C

**Conductor DC Resistance Unbalance:** ≤2% @ 20°C

**Pair to Ground Capacitance Unbalance:** ≤1200 pF / km

**Characteristic Impedance:** 100 Ohms nominal



#### (4) Shielded Twisted Pairs

**Colors:** Blue/white, orange/white, green/white, brown/white

**Conductors:** 22 AWG solid bare copper

**Insulation:** Foam PE

**Outer Diameter (per conductor):** 0.059 inch (1.5 mm) nominal

**Shield (per pair):** AL foil

#### Overall Shield

**Shield:** Tinned copper braid (>50% coverage)

#### Outer Jacket

**Color:** Violet

**Material:** LSZH

**Thickness:** 0.020 inch (0.5 mm)

**Outer Diameter:** 0.307 ±0.012 inch (7.8 ±0.3 mm)

**Minimum Recommended Bend Radius:** 2.46 inches (63 mm)

**Maximum Recommended Pull Tension:** 25 lbf (111 N)

#### Environmental

**Operating Temperature:** -4° to 140°F (-20° to 60°C)

#### Weight

**Bulk Cable Weight:** 42.74 lb / 1000 ft (63.6 kg / km)

#### Compliance

NEC Article 800, IEC 60332-1, IEC 61156-5, ISO/IEC 11801, Category 7a

# DM-CBL-ULTRA-LSZH DigitalMedia™ Ultra Cable, Low Smoke Zero Halogen

## MODELS & ACCESSORIES

### Available Models

---

**DM-CBL-ULTRA-LSZH-SP500:** DigitalMedia™ Ultra Cable, Low Smoke Zero Halogen, 500 ft spool (Available only in Europe)

**DM-CBL-ULTRA-LSZH-SP1000:** DigitalMedia™ Ultra Cable, Low Smoke Zero Halogen, 1000 ft spool (Available only in Europe)

### Available Accessories

---

**DM-CONN:** DigitalMedia™ Cable Connector

#### Notes:

1. DM-CONN connectors sold separately.

This product may be purchased from an authorized Crestron dealer. To find a dealer, please contact the Crestron sales representative for your area. A list of sales representatives is available online at [www.crestron.com/salesreps](http://www.crestron.com/salesreps) or by calling 800-237-2041.

The specific patents that cover Crestron products are listed online at: [patents.crestron.com](http://patents.crestron.com).

Crestron, the Crestron logo, DigitalMedia, DigitalMedia 8G+, DM, and DM 8G+ are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. HDBaseT is either a trademark or registered trademark of the HDBaseT Alliance in the United States and/or other countries. HDMI is either a trademark or registered trademark of HDMI Licensing LLC in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography. Specifications are subject to change without notice. ©2014 Crestron Electronics, Inc.