

DigitalMedia 8G™ Single-Mode Fiber Input Card w/Downmixing for DM® Switchers

- > Modular input card for a DM-MD8X8, DM-MD16X16, or DM-MD32X32 switcher
- > Provides a single DM 8G® SM Fiber input
- > Supports cable lengths up to 7.5 miles (12 km) using CresFiber® 8G SM or G.652.D single-mode fiber^[1]
- > Handles video resolutions up to Full HD 1080p
- > Handles computer resolutions up to WUXGA
- > Handles 3D video and Deep Color
- > Handles Dolby® TrueHD, DTS-HD®, and uncompressed 7.1 linear PCM audio
- > HDCP compliant
- > Includes an HDMI® output for pass-through of the input signal
- > Includes a stereo analog line-level audio output with volume control
- > Allows extraction of stereo 2-channel audio signals
- > Built-in downmixing enables simultaneous distribution of multi-channel surround sound and 2-channel stereo audio signals
- > Occupies a single DM Switcher input card slot
- > Provides a rack-mountable DM 8G Fiber receiver solution using the optional DMCI card interface^[2]

The DMC-S2 is an input card designed for use with any card-based Crestron® DigitalMedia™ Switcher. It provides one DM 8G® SM Fiber input, with associated HDMI® pass-through and analog audio outputs. The DM 8G SM Fiber input enables the connection of a DM 8G SM Fiber transmitter, or the output of another DM® switcher, using a single strand of single-mode fiber.^[1]

The DMC-S2-DSP provides all the features of the DMC-S2 with the addition of downmixing to enable the simultaneous distribution of multichannel 7.1 surround sound and 2-channel stereo signals. It is recommended for use with surround sound sources to allow the original multichannel signal to be distributed to rooms with surround sound systems, while simultaneously distributing a 2-channel downmix signal to stereo-only rooms and devices.

DigitalMedia 8G™ Single-Mode Fiber

Engineered for ultra high-bandwidth and ultimate scalability, DigitalMedia 8G Single-Mode Fiber (DM 8G SM Fiber) provides a true one-wire lossless transport for moving high-definition video, audio, Ethernet, and control signals over single-mode fiber. DM 8G SM Fiber handles uncompressed Full HD 1080p video signals with support for HDCP, Deep Color, 3D, and high-bitrate 7.1 audio, as well as computer signals up to WUXGA. All signals are transported over one strand of single-mode fiber, supporting distances up to 7.5 miles (12 km) using CresFiber® 8G SM or G.652.D single-mode fiber optic cable.^[1]

HDMI® Pass-Through

Every DM switcher input card includes an HDMI output port, which can be used to pass the input signal through to a local audio processor or video monitor, or to feed a second DM switcher for output expansion purposes.



Audio Extracting and Downmixing

The DMC-S2-DSP also includes an unbalanced analog audio output, allowing stereo audio signals to be extracted from the digital input and fed to a multiroom audio distribution system. Built-in DSP allows multi-channel surround sound signals to be decoded and downmixed to stereo. The stereo downmix signal is automatically routed to the analog output, and can also be routed via any switcher output for distribution to stereo-only displays and other equipment. The analog output includes volume control that is adjustable via a control system using a keypad, touch screen, handheld remote, or mobile device.

Standalone DM 8G SM Fiber Receiver

In addition to its use as an input card for DM switchers, the DMC-S2-DSP may also be used with the DMCI DigitalMedia Card Interface^[2] to provide a DM 8G SM Fiber receiver solution that's perfect for installation in an equipment rack or AV cart, or as a portable display interface.

To configure a DM switcher complete with input and output cards, cables, and other peripherals, please use the online [DigitalMedia Switcher Configuration Tool](#).

Please refer to the *DigitalMedia Resources Webpage* at <http://www.crestron.com/dmresources/> for additional design tools and reference documents.

SPECIFICATIONS

Video

Input Signal Types: DM 8G® SM Fiber (DigitalMedia™ over one single-mode fiber optic strand)^[1]

Output Signal Types: HDMI® or DVI^[3] to switcher backplane and HDMI OUT connector

Formats: DM 8G SM Fiber & HDMI w/Deep Color & 3D, DVI, HDCP content protection support

DMC-S2-DSP DigitalMedia 8G™ SM Fiber Input Card w/Downmixing for DM® Switchers

Input Resolutions, Progressive: 640x480@60Hz, 720x480@60Hz (480p), 720x576@50Hz (576p), 800x600@60Hz, 848x480@60Hz, 852x480@60Hz, 854x480@60Hz, 1024x768@60Hz, 1024x852@60Hz, 1024x1024@60Hz, 1280x720@50Hz (720p50), 1280x720@60Hz (720p60), 1280x768@60Hz, 1280x800@60Hz, 1280x960@60Hz, 1280x1024@60Hz, 1360x768@60Hz, 1365x1024@60Hz, 1366x768@60Hz, 1400x1050@60Hz, 1440x900@60Hz, 1600x900@60Hz, 1600x1200@60Hz, 1680x1050@60Hz, 1920x1080@24Hz (1080p24), 1920x1080@25Hz (1080p25), 1920x1080@50Hz (1080p50), 1920x1080@60Hz (1080p60), 1920x1200@60Hz, 2048x1080@24Hz, 2048x1152@60Hz, plus any other resolution allowed by HDMI up to 165MHz pixel clock

Input Resolutions, Interlaced: 720x480@30Hz (480i), 720x576@25Hz (576i), 1920x1080@25Hz (1080i25), 1920x1080@30Hz (1080i30), plus any other resolution allowed by HDMI up to 165MHz pixel clock

Output Resolutions: Matched to input

Audio

Input Signal Types: DM 8G SM Fiber

Output Signal Types: HDMI (simultaneous multichannel and 2-channel downmix) to switcher backplane, HDMI (multichannel pass-thru from input) at HDMI OUT, analog stereo 2-channel, allows audio breakaway

Digital Formats: Dolby® Digital, Dolby Digital EX, Dolby Digital Plus, Dolby TrueHD, DTS®, DTS-ES, DTS 96/24, DTS-HD High Res, DTS-HD Master Audio™, up to 8ch PCM

Analog Format: Stereo 2-channel

Decoder: Cirrus Logic® CS49700 HD Audio Decoder DSP with dual 32-bit cores

Digital-To-Analog Conversion: 24-bit 48 kHz

Performance (analog): Frequency Response: 20Hz to 20kHz ±0.5dB;
S/N Ratio: >95dB, 20Hz to 20kHz A-weighted;
THD+N: <0.005% @ 1kHz;
Stereo Separation: >90dB

Volume Gain Range (analog): -80dB to 0dB

Communications

DigitalMedia: DM 8G SM Fiber, HDCP, EDID, CEC, Ethernet

HDMI: HDCP, EDID, CEC

Connectors

HDMI OUT: (1) 19-pin Type A HDMI female;

HDMI digital video/audio output;

Also supports DVI^[3]

DM IN SMF/LC: (1) LC female optical fiber connector;

DM 8G Single-Mode Fiber input;

Connects to the DM 8G SM Fiber output of a DM transmitter or other DM device via CRESFIBER8G-SM single-mode fiber optic cable^[1]

AUDIO OUT: (2) RCA female;

Unbalanced stereo line-level audio output;

Output Impedance: 100 Ohms nominal;

Maximum Output Level: 2 Vrms

Indicators

DM IN SMF/LC: (1) green LED, indicates DM link status

Construction

Plug-in card, occupies (1) DM switcher input card slot, includes metal faceplate w/black finish

Weight

8.0 oz (227 g)

MODELS & ACCESSORIES

Available Models

DMC-S2-DSP: DigitalMedia 8G™ Single-Mode Fiber Input Card w/Downmixing for DM® Switchers

Available Accessories

CRESFIBER8G-SM-P: CresFiber® 8G Single-Mode Fiber Optic Cable, plenum

CRESFIBER8G-SM-CONN-LC-12: CresFiber® 8G Single-Mode Fiber Optic Cable Connector, LC, 12-Pack

CRESFIBER-TK: CresFiber® Termination Kit (AFL Telecommunications®)

CBL Series: Crestron® Certified Interface Cables

MP-WP Series: Media Presentation Wall Plates

MPI-WP Series: Media Presentation Wall Plates - International Version

DMCI: DigitalMedia™ Card Interface

Notes:

1. The maximum cable length for DigitalMedia 8G Single-Mode Fiber (DM 8G SM Fiber) is 7.5 miles (12 km) using Crestron CRESFIBER8G-SM or third-party G.652.D (or better) single-mode fiber optic cable. Refer to the [Crestron DigitalMedia Design Guide, Doc. #4546](#) for complete system design guidelines. All wire and cables are sold separately.
2. Item(s) sold separately.
3. DVI is supported via the HDMI output using a suitable adapter or interface cable. CBL-HD-DVI interface cables are available separately.

This product may be purchased from an authorized Crestron dealer. To find a dealer, please contact the Crestron sales representative for your area. A list of sales representatives is available online at www.crestron.com/salesreps or by calling 800-237-2041.

The specific patents that cover Crestron products are listed online at: patents.crestron.com.

Crestron, the Crestron logo, DigitalMedia, DigitalMedia 8G, DM, and DM 8G are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Cirrus Logic is either a trademark or registered trademark of Cirrus Logic, Inc. in the United States and/or other countries. Dolby and Dolby Digital are either trademarks or registered trademarks of Dolby Laboratories in the United States and/or other countries. DTS, DTS-HD, and DTS-HD Master Audio are either trademarks or registered trademarks of DTS, Inc. in the United States and/or other countries. HDMI and the HDMI Logo are either trademarks or registered trademarks of HDMI Licensing LLC in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography. Specifications are subject to change without notice. ©2014 Crestron Electronics, Inc.