

2-Channel DigitalMedia 8G™ Fiber Output Card for DM® Switchers

- > Modular output card for a DM-MD8X8, DM-MD16X16, or DM-MD32X32 switcher
- > Provides two independent DM 8G® Fiber outputs
- > Supports cable lengths up to 1000 ft (300 m) using CresFiber® 8G, or 500 ft (150 m) using other multimode fiber^[1]
- > Includes a parallel HDMI® port on the first output
- > Handles video resolutions up to Full HD 1080p
- > Handles computer resolutions up to WUXGA
- > Handles 3D video and Deep Color
- > Handles Dolby® TrueHD, DTS-HD®, and uncompressed 7.1 linear PCM audio
- > HDCP compliant
- > Occupies a single output card slot



The DMC-SO-HD is an output card designed for use with any card-based Crestron® DigitalMedia™ Switcher. It provides two independent DM 8G® Fiber outputs, plus one HDMI® output. The HDMI output carries the same signal as the first DM 8G Fiber output. Each DM 8G Fiber output enables connection to a DM 8G Fiber Receiver, or the input of another DM® switcher, using a single strand of multimode fiber.^[1]

All outputs on the DMC-SO-HD are capable of handling video resolutions up to Full HD 1080p, as well as computer resolutions up to WUXGA. DM 8G Fiber transports uncompressed high-definition video and computer signals over distances up to 1000 feet (300 m) using CresFiber® 8G, or 500 feet (150 m) using other multimode fiber optic cable.^[1]

To configure a DM switcher complete with input and output cards, cables, and other peripherals, please use the online [DigitalMedia Switcher Configuration Tool](#).

Please refer to the [DigitalMedia Resources Webpage at http://www.crestron.com/dmresources/](#) for additional design tools and reference documents.

SPECIFICATIONS

Video

Signal Types: DM 8G® Fiber (DigitalMedia™ over one multimode fiber optic strand), HDMI®, DVI^[2]

Formats: DM 8G Fiber & HDMI with Deep Color & 3D; HDCP content protection support

Resolutions, Progressive: 640x480@60Hz, 720x480@60Hz (480p), 720x576@50Hz (576p), 800x600@60Hz, 848x480@60Hz, 852x480@60Hz, 854x480@60Hz, 1024x768@60Hz, 1024x852@60Hz, 1024x1024@60Hz, 1280x720@50Hz (720p50), 1280x720@60Hz (720p60), 1280x768@60Hz, 1280x800@60Hz, 1280x960@60Hz, 1280x1024@60Hz, 1360x768@60Hz, 1365x1024@60Hz, 1366x768@60Hz, 1400x1050@60Hz, 1440x900@60Hz, 1600x900@60Hz, 1600x1200@60Hz, 1680x1050@60Hz, 1920x1080@24Hz (1080p24), 1920x1080@25Hz (1080p25), 1920x1080@50Hz (1080p50),

1920x1080@60Hz (1080p60), 1920x1200@60Hz, 2048x1080@24Hz, 2048x1152@60Hz, plus any other resolution allowed by HDMI up to 165MHz pixel clock

Resolutions, Interlaced: 720x480@30Hz (480i), 720x576@25Hz (576i), 1920x1080@25Hz (1080i25), 1920x1080@30Hz (1080i30), plus any other resolution allowed by HDMI up to 165MHz pixel clock

Audio

Signal Types: DM 8G Fiber, HDMI

Formats: Dolby Digital®, Dolby Digital EX, Dolby Digital Plus, Dolby® TrueHD, DTS®, DTS-ES, DTS 96/24, DTS-HD High Res, DTS-HD Master Audio™, up to 8ch PCM

Communications

DigitalMedia: DM 8G Fiber, HDCP, EDID, CEC, Ethernet

HDMI: HDCP, EDID, CEC

Connectors

MMF/SC: (2) SC female optical fiber connectors, comprising (2) DM 8G Fiber outputs;

Each connects to the DM 8G Fiber input of a DM receiver or other DM device via CresFiber® 8G fiber optic cable ^[1]

HDMI: (1) 19-pin Type A HDMI, female;

HDMI digital video/audio output, DVI compatible^[2];

Outputs same signal as the left DM 8G Fiber output

Indicators

MMF/SC: (2) green LEDs, indicate DM link status for each corresponding DM 8G Fiber output

Construction

Plug-in card, occupies (1) DM switcher output card slot, includes metal faceplate w/black finish

DMC-SO-HD 2-Channel DigitalMedia 8G™ Fiber Output Card for DM® Switchers

Weight

6.2 oz (176 g)

MODELS & ACCESSORIES

Available Models

DMC-SO-HD: 2-Channel DigitalMedia 8G™ Fiber Output Card for DM® Switchers

Available Accessories

CRESFIBER8G-NP: CresFiber® 8G Multimode Fiber Optic Cable, 50/125 x4 breakout, non-plenum

CRESFIBER8G-P: CresFiber® 8G Multimode Fiber Optic Cable, 50/125 x4 breakout, plenum

CRESFIBER-CONN-SC50UM-12: CresFiber® Fiber Optic Cable Connector (AFL Telecommunications®), SC 50µm, 12-Pack

CRESFIBER-TK: CresFiber® Termination Kit (AFL Telecommunications®)

CRESFIBER-SINGLE-SC-P: CresFiber® Simplex Fiber Optic Cable Assembly, 50/125, SC, Plenum

CRESFIBER-SINGLE-SC-ARMORED-P: CresFiber® ARMORED Simplex Fiber Optic Cable Assembly, 50/125, SC, Armored, Plenum

CRESFIBER-SINGLE-SC-CLEAR-NP-100: CresFiber® CLEAR Simplex Fiber Optic Cable Assembly, 50/125, SC, Non-Plenum

CBL Series: Crestron® Certified Interface Cables

MP-WP Series: Media Presentation Wall Plates

MPI-WP Series: Media Presentation Wall Plates - International Version

Notes:

1. The maximum cable length for DigitalMedia 8G Fiber (DM 8G Fiber) is 1000 ft (300 m) using [CRESFIBER8G](#) fiber optic cable, or 500 ft (150 m) using standard [CRESFIBER](#), [CRESFIBER-SINGLE-SC](#), or third-party OM3 simplex multimode fiber optic cable. Refer to the [Crestron DigitalMedia Design Guide, Doc. #4546](#) for complete system design guidelines. All wire and cables are sold separately.
2. DVI is supported via the HDMI output using a suitable adapter or interface cable. [CBL-HD-DVI](#) interface cables are available separately.

This product may be purchased from an authorized Crestron dealer. To find a dealer, please contact the Crestron sales representative for your area. A list of sales representatives is available online at www.crestron.com/salesreps or by calling 800-237-2041.

The specific patents that cover Crestron products are listed online at: patents.crestron.com.

Crestron, the Crestron logo, CresFiber, DigitalMedia, DigitalMedia 8G, DM, and DM 8G are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Dolby and Dolby Digital are either trademarks or registered trademarks of Dolby Laboratories in the United States and/or other countries. DTS, DTS-HD, and DTS-HD Master Audio are either trademarks or registered trademarks of DTS, Inc. in the United States and/or other countries. HDMI is either a trademark or registered trademark of HDMI Licensing LLC in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography. Specifications are subject to change without notice. ©2014 Crestron Electronics, Inc.